

| Bend Entriannet Surger Projector - X1300 Sine Display End Call | | |
|---|---|---|
| 3000000000000000000000000000000000000 | BenQ Entertainment Gan | ning Projector - X1300i |
| Name of the second se | Feature Highlight | |
| *********************************** | | Personal Action of the Action |
| ************************************ | | |
| ************************************ | | |
| Production to the set of the se | * HDR Game Compatibility | |
| Hit origination with a set of the set | * GameMaestro - Immersive Audio-Visual (| Game modes |
| SequencePresenceP | * treVolo Steroe Speakers w/ Bongiovi DPS | S Technology |
| Diple Proceedings Proceedings Proceedings Proceedings <t< td=""><td>* LED Long Lasting Color Performance</td><td>Serve Hubble</td></t<> | * LED Long Lasting Color Performance | Serve Hubble |
| Diple Proceedings Proceedings Proceedings Proceedings <t< td=""><td>* Google certificated android TV dongle -</td><td>0501</td></t<> | * Google certificated android TV dongle - | 0501 |
| <table-container>NumentationDPPProgrammentation<!--</td--><td>0 0</td><td>••••</td></table-container> | 0 0 | •••• |
| <table-container><math><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></math></table-container> | • • | |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | | |
| <table-container><table-container><table-container>margenericNote of the second s</table-container></table-container></table-container> | DMD type | 0.65" |
| <table-container><math><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></math></table-container> | Native Resolution | 1080p (1920 x 1080) |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | Brightness | 3000 ANSI Lumens |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | Contrast Ratio* | 500,000:1 (Dynamic Black) |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | Display Color | |
| <table-container><table-container>IndemIDinstructionID<</table-container></table-container> | | |
| generationReading a second secon | | |
| <table-container> BC3 D000 bins PGICA Toreafine Some frag Come frag</table-container> | | |
| OpticalJ:SI (101°) (217 m) Zone MainJ:SI (217 m) Zon | Light Source life** | ECO 30,000 hours |
| Two stars1.5 (100 (2.27 m)Some stars1.7 aSome stars1.7 aLena1.7 aLena1.7 aMay conserved (2.27 a)1.7 aMycors of Mar1.7 aMycors of M | | unar (ECo 20,000 null) |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | | 12 15(/ (00% @ 2.0.2 m) |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | | |
| <table-container><table-container><table-container>IndexNameRoser Addition3.0Roser Addition3.0Rose</table-container></table-container></table-container> | | |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | | |
| <table-container>Physical space7%Precent1000000000000000000000000000000000000</table-container> | | |
| Picture Picture <t< td=""><td>Projection Offset</td><td>91.7%</td></t<> | Projection Offset | 91.7% |
| Picture Picture <t< td=""><td></td><td></td></t<> | | |
| <table-container> Reser Hole Bight / Ling Room / Gove / Sports / Cinema / (3D) / (HDR IGne) / (HGR / User Room Hole Bight / Ling Room / Gove / Sports / Cinema / (3D) / (HDR IGne) / (HGR / User Room Hole Review Conception With Conception With Conception Station Space With Conception With Conception Station Space With Conception With Conception Station Space Insert Reservance With Conception Station Space Conception With Conception Station Space Conception With Conception Station Space Conception With Conception Station Space Station Space Station Station Space Conception Station Station Space Station Space Station Station Space Station A Propagains Space Station Space Station Space</table-container> | | |
| Game Mode RPG Game/ SPG Game/ Sec.795 Coverage Syst Audo Sec.795 Coverage Syst 2 (Chamber Speaker by treV(s)) Special Feature Sec.795 Coverage Sec.795 Coverage Special Feature Sec.795 Coverage Sec.795 Coverage Special Feature Hom (0.3 and) Sec.795 Coverage Special Feature Sec.795 Coverage Sec.795 Coverage Version Sance Sec.795 Coverage Sec.795 Coverage Special Feature NA Sec.795 Coverage Sec.795 Coverage Sec.795 Coverage | | Brinkr / Living Room / Game / Sports / Cinema / (3D) / (HDR I0) / (HDR Game) / (HI G) / Liser |
| Ret. 70 Goving 98: Audio 99: School Sector 99:20 (Camber Spake by treVice) Sector Sector 99:00 (Camber Spake by treVice) Sector Sec | | |
| Aduit Special Feature Special Feature Security Bart, Kesnington lock. Security Special Feature Security Bart, Kesnington lock. Special Feature HDR.10. HLG. 3D, SamePhateuro, Autor Krystone Compatibility HDR.10. HLG. 3D, SamePhateuro, Autor Krystone Compatibility VGA (edv x 400) to 4K UHD (840 x 2160) Horizonal Frequency ISX-135KHz Vertical Sca Rate 21-10Hz Volk Compatibility NA Vertical Sca Rate 21-10Hz Volk Compatibility NA Vertical Sca Rate 21-10Hz Vertical Sca Rate 21-10Hz Vertical Sca Rate 21-10Hz Vertical Sca Rate 21-10Hz Consol Compatibility NA Vertical Sca Rate 21-10Hz Consol Compatibility NA Route Compatibility NA Route Compatibility NA Route Compatibility Assoc Max Xoas Cons Sca Cons | | |
| <table-container><table-container>Baters and part of the second part of the second</table-container></table-container> | | |
| <table-container>SpecificationSecond part of the second part</table-container> | | 5W x 2 (Chamber Speaker by treVolo) |
| Security Security Bar, Kenington lock Input Leg ⁴⁴ I fame (33m) Input Leg ⁴⁴ I PAND (H.G. 2D, came*hastro, Auto Keystone Compatibility UPAND (H.G. 2D, came*hastro, Auto Keystone Compatibility Sch (35K) Versical Sara Race 23-120+2 Versical Sara Race 23-120+2 Versical Sara Race 24-00 Versical Sara Race 28-00 Versical Sara Race 29-00 Versical Sara Race 20-00 Versical Sara Race 20-00 Versical Sara Race 20-00 Power Sarph A (100-1400 (SufOdH) Sarady Power Camupation 12-125 Saram (Versical Saram Kege) Power Card Ray Race Market Ref Power Card | | |
| Processor IDER/DE. PLOS. D.G. BandMadestro. Auto. Keystone Compute Eventor Resolution. Support VGA. (40 x. 400) to 4K UHD (3840 x. 2160) Morizontal Frequency Disk. 135KHz Visition Sampara Disk. 135KHz Visition Sampara Sampara Morizontal Frequency Na Console Game Compatibility Resolution 4. Respiration 4. Respiration 5. Resolution 4. Respiration 5. Resolution 4. Respiration 4. Respiration 5. Resolution 4. Respiration 5. Resolution 4. Respiration 4. Respiration 5. Resolution 4. Respiration 4. Respiration 4. Respiration 5. Resolution 4. Respiration 4. Respiratin 4. Respiration 4. Respiratin 4. Respiratin 4. Respi | • | Security Bar, Kensington lock |
| Procession IDRID, HLG, 3D, SameMaetro, Auto Keystone Compatibility IDRID, HLG, 3D, SameMaetro, Auto Keystone Resolution Signory VGA (40 x 400) to 4K UHD (380 x 2160) Marcina Ma | | |
| Compatibility VGA (04 x 400 in 4K UHD (240 x 2160) Neriorand Frequery ISK 13KHa Vertical San Rata 3120Ha Vertical San Rata Aveb 576, 5769, 7009, 1000, 10009, 21609 Vertical San Rata Paystation 4, Phystation 3Im Console Game Compatibility Phystation 4, Phystation 3Im Nata Phystation 4, Phystation 4, Phystation 3Im Schoole X, Xbox One S Nata Power Singly Aveb 700 (506 0Hz) Station 4, Cone X, Xbox One S Nata Station 4, Phystation 4, Phystation 3Im Nata Schoole X, Xbox One S Nata Station 4, Cone X, Yo Station 4, Cone X, Stati | | |
| Readom Support Gel (40 ex 000 ex 00 ULP) (300 ex 100 ULP) (300 ex 100 ex 100 ULP)) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe 32 - 100 ex 100 ULP) Vertical Stan Exe Exe 32 - 100 Exe | | TIDINTO, FILO, JD, ORIFET RESULO, PALO REJISIONE |
| Hindux BrequeveIsiSBK#Veriotal San Rev3/104Veriotal San | | VGA (640 x 480) to 4K UHD (3840 x 2160) |
| Vertical Scan Roy 23-120Hz Vertical Scan Roy 480, 480p, 576, 576p, 720p, 1080, 1080p, 2160p HDTV Compatibility 480, 480p, 576, 576p, 720p, 1080, 1080p, 2160p Video Compatibility Phystation 4Pn, Phystation Sim XBox One X, Xbox One S Nemedo Switch Power Power Power Supply AC 100 - 240V (50/60Hz) Standor Poor Supprion 40.5000 - 260V Power Consumption(Phar/Normal/Eco Na S60VV, Normal 330V, Eco 160V Dimension Advertion 40.5000 - 260V Product Dimension (Wsthzb) 72x 197.1 x 259 Anni (wlo adjustment feet) Product Wreight 64.8 (r 14.1 lbs Operating Tompara 0-40 agrees (celcus) Porectore - Operating Company 0-40 agrees (Celcus) Protectore - Accessories (Standard) Benoty Chotol & Stattop) x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD4000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD40000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD40000) Protectore - RCIOB & Mattery x 1 (SJ, I/SD400000000) <td></td> <td></td> | | |
| HVT Compatibility 480, 480, 576, 576, 720, 1080, 1080, 2160 Video Compatibility NA Console Game Compatibility Napstation 4, Paystation Sim XBoo. One S. Xboo. One S. Nitendo Switch Power Sum of No. 58, 576, 720, 1080, 1080, 2160 | | |
| Vide CompatibilityNAConside Same Same Same Same Same Same Same Sam | | |
| Casale Game Compatibility Pisstation 4. Pisstation 3. | | |
| XBox One X, Xbox One S Nitendo Switch Power Power Sorphy AC 100 ~ 240V (50/60Hz) Power Consumption (Max/Normal/Eo) Max 360W, Normal 330W, Eco 160W Standby Power Comsumption 4.50W Dimension and Weight Product Weight 6.10V - 240V (50/60Hz) Operation Condition Product Weight 6.42 14.1 1bs Operating Temperature 0-40 degrees (Celcius) Accessories Accessories (Standard) Senote Control - RCI068 w/ Battery x I (5J,JKC06.001) Benot HDMI Video Streaming (C9C01) x I (5J,JHC14.001) Power Cord (by region) X I (18M) Power Cord (by regi | | |
| Network Powe Powe (0) Coloradio (0) Sona (0) Coloradio (0 | Console Game Compatibility | |
| Power Supply AC 100 - 240V (50/60Hz) Power Supply AC 100 - 240V (50/60Hz) Max 360W, Normal 330W, Eco 166W Standby Power Comsumption (Max/Normal/Eco) 4.55W Standby Power Comsumption (Max/Normal/Eco) Dimension and Weight 72 x 197.1 x 259.4mm (w/o adjustment feet) The second s | | |
| Prover Supply AC 100 ~ 240V (50/60Hz) Power Consumption (Max/Normal/Eco) Max 360W, Normal 330W, Eco 160W Standby Power Consumption < 0.5W Dimession and Weight Product Dimensions (WxHzD) 271x 197.1 s25.4mm (w/o adjustment feet) Operation Condition 272x 197.1 s25.4mm (w/o adjustment feet) Noise Level(Normal/ECO) 31/27d PA Operation Condition 1/27d PA Product Noise Level(Normal/ECO) 0.40 degrees (Celcius) Accessories (Standard) Remote Control - RCI06de w/ Battry x1 (51/KC06.001) Beney HDMI video Stremming (QSDI) x1 (51/JH314.001) Power Cord (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Quick Start Guides x1 (211, Warrange Card (by region) x1 (163/H) Power Card (by region) x1 (163/H) Power Card (by re | Power | |
| Normal/Eco Max 360/V, Normal 330/V, Eco 160/V Standby Power Consumption < 0.5/V | | AC 100 ~ 240V (50/60H-) |
| Standay Power Consumption <05W | | |
| Product Dimensions and Weight 72 x 197.1 x 259.4mm (w/o adjustment feet) Product Dimensions (WxHxD) 272 x 197.1 x 259.4mm (w/o adjustment feet) Product Weight 6.4 kg / 14.1 lbs Operation Condition 10.2 XPL Noise Level(Normal/ECO) 9.1727dBA Operation Emperature 0-40 degrees (Celclus) Accessories Accessories (Standard) Remote Control - RCI068 w/ Battery x 1 (5/JKC06.001) BenQ HDMI Video Streaming (QS01) x 1 (5/JH314.001) Power Cord (by region) x 1(.18M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD - On Screen Display Language Arabic/Butgrian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hind/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguesed Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) | | |
| Product Dimensions (WXHZ) 272 x 197.1 x 259.4mm (w/o adjustment feet) Product Weight 6.4 kg / 14.1 lbs Operation Condition Noise Level(Normal/ECO) 31/27dBA Operating Temperature 0-40 degrees (Celcius) Accessories Accessories (Standard) Remote Control - RCI068 w/ Battery x 1 (5J,JKC06.001) Beneq HDMI Video Streaming (QS01) x 1 (5J,JH314.001) Power Cord (by region) x 1 (1.8M) Quick Start Guide x 1 (21L) Varianty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD On Screen Display Language Arabit/Bugrain/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Environment Notice | Standby Power Comsumption | < 0.5W |
| Product Weight 64 kg / 14.1 kg Operation Condition 1/27 dBA Noise Level(Normal/ECO) 31/27 dBA Operating Temperature 0-40 degrees (Celcius) Accessories Emote Control - RCI068 w/ Battery x 1 (5J,JKC06.001) BerQ HDMI Video Streaming (QS01) x 1 (5J,JH314.001) Power Cord (by region) x 1 (1.8M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) D Glasses Magnetic-adjustment feet ODS | Dimension and Weight | |
| Operation Condition Noise Level(Normal/ECO) 31/27dBA Operating Temperature 0~40 degrees (Celcius) Accessories Accessories Accessories (Standard) Remote Control - RCI068 w/ Battery x 1 (5J,JKC06.001) BenQ HDM1 Video Streaming (QS01) x 1 (5J,JH314.001) Power Cord (by region) x 1(1.8M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD | Product Dimensions (WxHxD) | 272 x 197.1 x 259.4mm (w/o adjustment feet) |
| Operation Condition Noise Level(Normal/ECO) 31/27dBA Operating Temperature 0~40 degrees (Celcius) Accessories Accessories Accessories (Standard) Remote Control - RCI068 w/ Battery x 1 (5J,JKC06.001) BenQ HDM1 Video Streaming (QS01) x 1 (5J,JH314.001) Power Cord (by region) x 1(1.8M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD | Product Weight | 6.4 kg / 14.1 lbs |
| Noise Level(Normal/ECO) 3/127dBA Operating Temperature 0~40 degrees (Celcius) Accessories Accessories (Standard) Remote Control - RCI068 w/ Battery x 1 (5/J,KC06.001) BenQ HDMI Video Streaming (QS01) x 1 (3/J,H314.001) Power Cord (by region) x (1.8M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) BG Glasses Magnetic-adjustment feet OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hind/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portugueses Environment Notice | - | |
| Operating Temperature 0~40 degrees (Celcius) Accessories Emote Control - RCI068 w/ Battery x 1 (SJ,JKC06.001) BenQ HDMI Video Streaming (QS01) x 1 (SJ,JH314.001) BenQ HDMI Video Streaming (QS01) x 1 (SJ,JH314.001) Very arrany Card (by region) x (1.8M) Quick Start Guide x 1 (21L) Varrany Card (by region) x (0.9M) BenQ HDMI Video Streaming (QS01) x 1 (SJ,H314.001) Accessories (Optional) D Glasses Magnetic-adjustment feet Magnetic-adjustment feet OSD variany Cardia / Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portugueses Environment Notice Variany Card (by region) / Variany Cardia (Croatian/ Czech/ Danish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) | • | 21/2749.6 |
| Accessories Remote Control - RCI068 w/ Battery x I (5J,JKC06.001) BenQ HDMI Video Streaming (QS01) x I (5J,JK206.001) BenQ HDMI Video Streaming (QS01) x I (5J,JH314.001) Power Cord (by region) x (1.8M) Quick Start Guide x I (21L) Warranty Card (by region) Power Cord (by region) x (1.8M) Quick Start Guide x I (21L) Warranty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD | | |
| Accessories (Standard) Remote Control - RC1068 w/ Battery x 1 (5/,JKC06.001) BenQ HDMI Video Streaming (QS01) x 1 (5/,JH314.001) Power Cord (by region) x 1(1.8M) Quick Start Guide x 1 (2L) Warrancy Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD | | U~40 degrees (Cercius) |
| BenQ HDMI Video Streaming (QS01) x 1 (5),IH314.001) Power Cord (by region) x 1 (5),IH314.001) Power Cord (by region) x 11,8M) Quick Start Guide x 1 (21L) Warnety Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD On Screen Display Language Analysian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | | Remote Control - RCI068 w/ Rattery v 1 /SI IKC06 001) |
| Power Cord (by region) x 1 (1.8M) Quick Start Guide x 1 (21L) Warranty Card (by region) Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Environment Notice | necessories (stanuaru) | |
| Quick Start Guide x I (21L) Warranty Card (by region) Accessories (Optional) D Glasses Magnetic-adjustment feet OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Environment Notice | | |
| Accessories (Optional) 3D Glasses Magnetic-adjustment feet OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | | Quick Start Guide x I (21L) |
| Magnetic-adjustment feet OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | | Warranty Card (by region) |
| OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | | 2D Classes |
| On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | Accessories (Optional) | |
| Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) Environment Notice | | |
| Environment Notice | OSD | Magnetic-adjustment feet |
| | OSD | Magnetic-adjustment feet Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ |
| * The Contrast is measured by Full On Full Off standard. | OSD On Screen Display Language | Magnetic-adjustment feet Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ |
| The contracts is merced by an original original original and the second se | OSD On Screen Display Language Environment Notice | Magnetic-adjustment feet Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) |



External




Internal (Hidden space for ATV dongle)



| | | Qty |
|----|--|-----|
| Т | HDMI (2.0b, HDCP2.2) | 1 |
| 2 | HDMI (2.0b, HDCP2.2) - (support Audio Return) | 1 |
| 3 | DC 12V Trigger (3.5mm Jack) | I. |
| 4 | USB TypeA (5V/2.5A power, Service) | 1 |
| 5 | Audio out (S/PDIF) - (support 2 / 5.1-channel audio) | I. |
| 6 | RS232 In (D-sub 9pin, male) | Т |
| 7 | Audio out (mini jack) | I. |
| 8 | Kensington anti-theft lock slot | I. |
| 9 | IR Receiver (Front+Back) | 2 |
| 10 | Hidden Space for ATV dongle | |
| | - HDMI (2.0b, HDCP2.2) | 1 |
| | - micro USB cable (5V/1.5A power) | 1 |
| | | |

Installation



The screen aspect ratio is 16:9 and the projected picture is in 16:9 aspect ratio

| Screen size | | | | Distance from screen (mm) | | | | |
|-------------|------|--------|---------------|---------------------------|---------|----------------|---|--|
| Diagonal | | | | Min length | | Max length | Vertical offset (Lowest/Highest lens | |
| Inch | mm | H (mm) | W (mm) | (max. zoom) | Average | (min. zoom) | position) (mm) | |
| 30 | 762 | 374 | 664 | 863 | 950 | 1036 | -31 | |
| 40 | 1016 | 498 | 886 | 1151 | 1266 | 1381 | -42 | |
| 50 | 1270 | 623 | 1107 | 1439 | 1583 | 1727 | -52 | |
| 60 | 1524 | 747 | 1328 | 1727 | 1899 | 2072 | -62 | |
| 70 | 1778 | 872 | 1550 | 2015 | 2216 | 2417 | -73 | |
| 80 | 2032 | 996 | 1771 | 2302 | 2533 | 2763 | -83 | |
| 90 | 2286 | 1121 | 1992 | 2590 | 2849 | 3108 | -93 | |
| 100 | 2540 | 1245 | 2214 | 2878 | 3166 | 3454 | -104 | |
| 110 | 2794 | 1370 | 2435 | 3166 | 3482 | 3799 | -114 | |
| 120 | 3048 | 1494 | 2657 | 3454 | 3799 | 4144 | -125 | |
| 130 | 3302 | 1619 | 2878 | 3741 | 4115 | 4490 | -135 | |
| 140 | 3556 | 1743 | 3099 | 4029 | 4432 | 4835 | -145 | |
| 150 | 3810 | 1868 | 3321 | 4317 | 4749 | 5180 | -156 | |
| 160 | 4064 | 1992 | 3542 | 4605 | 5065 | 5526 | -166 | |
| 170 | 4318 | 2117 | 3763 | 4893 | 5382 | 5871 | -177 | |
| 180 | 4572 | 2241 | 3985 | 5180 | 5698 | 6216 | -187 | |
| 190 | 4826 | 2366 | 4206 | 5468 | 6015 | 6562 | -197 | |
| 200 | 5080 | 2491 | 4428 | 5756 | 6331 | 6907 | -208 | |
| 210 | 5334 | 2615 | 4649 | 6044 | 6648 | 7252 | -218 | |
| 220 | 5588 | 2740 | 4870 | 6331 | 6965 | 7598 | -228 | |
| 230 | 5842 | 2864 | 5092 | 6619 | 7281 | 7943 | -239 | |
| 240 | 6096 | 2989 | 5313 | 6907 | 7598 | 8288 | -249 | |
| 250 | 6350 | 3113 | 5535 | 7195 | 7914 | 8634 | -260 | |
| 260 | 6604 | 3238 | 5756 | 7483 | 8231 | 8979 | -270 | |
| 270 | 6858 | 3362 | 5977 | 7770 | 8547 | 9325 | -280 | |
| 280 | 7112 | 3487 | 6199 | 8058 | 8864 | 9670 | -291 | |
| 290 | 7366 | 3611 | 6420 | 8346 | 9181 | 10015 | -301 | |
| 300 | 7620 | 3736 | 6641 | 8634 | 9497 | 10361 | -312 | |





Special Stands w/ optional Adjustment feet



Feature icons

