



LH550

BenQ DLP Projector

- 2600 ANSI Lumens LED New Light Source
- 1080p High Native Resolution for Crisp Readability
- Up to 30,000 hrs LED Light Source Life on Eco Mode
- All Glass Lens Array for Pure Clarity




Display	
Projection System	DLP Single 0.65"
DMD Type	DC3 DMD Chip
Native Resolution	1080p (1920 x 1080)
Brightness	2600 ANSI Lumens
Contrast Ratio*	15,000 : 1
Aspect Ratio	Native 16:9 (5 Aspect Ratio Selectable)
Light Source	LED
Picture Mode	Bright/Presentation/Spreadsheet/sRGB/Video/(3D)/User 1/User 2
Light Source Life** (Normal/Eco/SmartEco®)	20,000/30,000/30,000 hours
Optical	
Throw Ratio	1.49-1.64
Zoom Ratio	1.1x
Keystone Correction	2D Vertical & Horizontal ±30 degrees, 1D Vertical Auto Keystone
Projection Offset	103% (Mode B) ± 2.5%
Projection Size	Wide: 70"~150", Tele: 70"~135"
Audio	
Built-In Speaker	10W x1
Special Feature	
Security	Security Bar, Kensington lock
Compatibility	
Resolution Support	VGA (640 x 480) to WUXGA (1920 x 1200)
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Power	
Power Consumption (100V)	215W
Standby Power Consumption	Normal < 0.5W
Power Supply	100 ~ 240V AC, 50/60 Hz
Dimension and Weight	
Product Dimensions (WxHxD)	303.5 x 220.7 x 107.4mm
Product Weight	2.6Kg
Operation Condition	
Noise Level (Normal/Eco)	Normal: 34 dBA @25°C (table center), Eco2 mode: 32 dBA @25°C (table center), Eco: 28 dBA @25°C (table center)
Operating Temperature	0 ~ 40°C
Accessories	
Accessories (Standard)	Remote control (5J.JND06.001), 1x Power Cord 1.8m (by region), Warranty Card (by region), QSG (4D.JRV01.001), User Manual E-edition
Accessories (Optional)	3D Glasses (5J.J9H25.002), Ceiling mount, Carry bag
OSD	
On Screen Display Language	Arabic/Bulgarian/Croatian/Czech/Danish/Dutch/English/Finnish/French/German/Greek/Hindi/Hungarian/Italian/Indonesian/Japanese/Korean/Norwegian/Polish/Portuguese/Romanian/Russian/Simplified Chinese/Spanish/Swedish/Turkish/Thai/Traditional Chinese/Farsi/Vietnamese (30 Languages)
Other	
Part Number	9H.JRV77.13E
EAN Code	471 8755 09117 9


* The Contrast is measured by Full On/Full Off standard.

** Light Source Life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.


INPUT AND OUTPUT TERMINALS



DIMENSIONS



PROJECTION DIMENSIONS




DISTANCE CHART

Screen Size				Projection Distance (mm)			
Diagonal		H (mm)	W (mm)	Min distance (with max zoom)	Average	Max distance (with min zoom)	Offset (mm)
Inch	mm						
30	762	374	664	990	1039	1089	11
40	1016	498	886	1319	1386	1452	15
50	1270	623	1107	1649	1732	1815	19
60	1524	747	1328	1979	2079	2178	22
70	1778	872	1550	2309	2425	2541	26
80	2032	996	1771	2639	2772	2905	30
90	2286	1121	1992	2969	3118	3628	34
100	2540	1245	2214	3299	3465	3631	37
110	2794	1370	2435	3628	3811	3994	41
120	3048	1494	2657	3958	4158	4357	45
130	3302	1619	2878	4288	4504	4720	49
140	3556	1743	3099	4618	4850	5083	52
150	3810	1868	3321	4948	5197	5446	56
160	4064	1992	3542	5278	5543	5809	60
170	4318	2117	3763	5608	5890	6172	64
180	4572	2241	3985	5937	6236	6535	67
190	4826	2366	4206	6267	6583	6898	71
200	5080	2491	4428	6597	6929	7261	75

CEILING / WALL MOUNT CHART

Ceiling/Wall mount screw: M4
(Max L = 25 mm; Min L = 20 mm)

Unit: mm



To optimize the projection quality, we suggest to project images in an area without grayscale.



benq.eu/en-eu/business/projector.html

BenQ

© 2023 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.