Beng

BenQ Europe B.V.

Meerenakkerweg I-17, 5652 AR Eindhoven, The Netherlands Tel: +31-88-888-9200 Fax: +31-88-888-9299

BenQ Nordic AB

Box 1072 Norgegatan I 16432 Krista,

Tel: +46-8-588-988-00

BenQ Austria GmbH

Central & Eastern Europe Altmannsdorfer Strasse 89 Top 6 I I 20 Vienna Tel: +43-1-38-00-300

BenQ UK Ltd. 3 Staplehurst Office Centre, Bicester Oxfordshire OX25

United Kingdom Tel: +44-870-850-4417 Fax: +44-870-850-4418

Fax: +43-1-38-00-399

BenQ Deutschland GmbH

BenQ Italy S.r.l.

Viale E. Marelli 165, 20099 Sesto San Giovanni (MI)

Italy Tel: +39-02-3664-3740

Essener Straße 5 46047 Oberhausen Germany Tel: +49-208-409-42-0 Fax: +49-208-409-42-99

I 200 Vienna Tel: +43-190-7276-0

BenQ Deutschland GmbH

Niederlassung Österreich Wehlistraße 27b / Stg. 2 / Top 5

BenQ France SAS La Boursidière RN186 92357 Le Plessis-Robinson Tel: +33-0-1-7037-1717

Calle Constitucion, 3 (2-1) 08960 Sant Just Desvern Tel: +34-93-556-0800 Fax: +34-93-556-0899

BenQ Deutschland GmbH

Täfernstrasse 32

5045 Baden-Dättwil

Tel: +41-44-74399-99

Fax: +41-44-74399-00

BenQTechnology Iberica S.L.U. BenQ Europe B.V.

Representative Office in Russia Park Place Moscow, 113/1 Leninsky, Prospekt B-101, 117198 Moscow

BenQ Benelux B.V.

Meerenakkerweg I-17, 5652 AR Eindhoven,

The Netherlands
Tel: +31-88-888-9200


Fax: +31-88-888-9299

Russia Tel: +7-095-937-8532 Fax: +7-095-626-5196

























Spark collaboration Get more work done

Transform your meetings with an intuitive 4K anti-glare display that lets you present, collaborate, and make video calls all in one place. More than just crisp visuals, the BenQ CS series offers tools and features that simplify setups and foster highly collaborative discussions.



We've made it easy for you to present

We've taken out all things that can steal your time and take focus off your presentation.

The CS simplifies meeting preparations by removing the need for wires, drives, and even laptops.



Flawless wireless projection

Tired of cables? With the CS, you can wirelessly share up to nine screens using InstaShare.

Control every session

Use the remote as a clicker, cursor, or floating tool toggle for easy annotation and recording.





Access files on the fly

Open and edit your cloud files on the CS through BenQ's Account Management System (AMS) and WPS.

More ways to collaborate

Do more than just present. With multiple built-in features made for effective coworking, you can maximize your meeting time and use the CS display as a functional collaborative workspace.



Work with any platform

Use specialized software from your slot-in computer or external device via the Duo OS window.

Be on the same page

No need to switch from app to app. Duo Windows lets you simultaneously work on two apps side-by-side.





Get hands on with work

Teams can add notes and media on the EZWrite whiteboard via their own devices for better collaboration.

2

Versatile video conferencing that meets all your needs

The CS and its OPS slot-in computer pair perfectly with popular video conferencing solutions such as Zoom Rooms, Microsoft Teams, Google Meet, Cisco Webex, and LogMeln GoToMeeting. You can also load the pre-installed TeamViewer Meeting for instant video conferencing.



Suitable for all meeting spaces

Designed for versatility, the CS pairs with different enterprise-grade conference cameras that are perfect for meeting rooms of any size.



DVY21 compact full HD webcam for huddle spaces



DVY22 smart 4K camera for midsize meeting rooms







DVY23 20x zoom PTZ camera for large conference rooms



Informed and always ready

Rooms? Announcements? We've got you covered. The CS series has integrated solutions that let you reserve rooms in advance and keep teams up to speed.





Book rooms with ease

Reserve displays via MeetingRoom365 while simultaneously sending out meeting invites.* The widget keeps everyone up to date about upcoming meetings and room schedules.

*You can use MeetingRoom365 with Microsoft Outlook, Microsoft Office 365, Microsoft Exchange, and Google Workspace.



Push instant notifications

Keep your coworkers in the know. For timely and important announcements, you can use X-Sign Broadcast to push messages to one or more meeting room displays in your office.

4



Management simplified

Free yourself from fuss. We've streamlined device and user management for you so you can focus on things that matter more.



Hassle-free management

Whether local or remote, you can install apps or centrally monitor, manage, and update multiple displays with ease through the BenQ Device Management Solution (DMS).



Easy user management

Add users and edit permissions for all your displays in just one go. BenQ's Identity and Access Management (IAM) system syncs with your AD server for seamless user management.



Data and device protection

Defend your displays against malware, roque apps, and malicious sites, while securing your corporate date. BenQ offers you IoT security through McAfee Mobile Security.



Control at your fingertips

Already on Extron? Then there's no need to switch. The CS fully integrates with Extron so you can easily adjust your displays to your liking without ever having to change system controllers.



Real-time troubleshooting

Need technical support? Save your administrators time and effort by utilizing TeamViewer on your display to conduct real-time remote assessment and troubleshooting.



Virtual workspace access

With the VMware Horizon Client, you can pull up any of your virtual desktops on the CS to get instant access to your hosted apps, files, and folders anytime during a meeting.

Specifications

Model			CS6501	CS7501	CS8601
Panel	Screen Size		65"	75"	86"
	Resolution		UHD 3840 × 2160	UHD 3840 x 2160	UHD 3840 × 2160
	Brightness (Typ.)		450	450	450
	Contrast Ratio (Typ.)		1200 : 1	1200 : 1	1200 : 1
	Viewing Angle (H/V)		178 degree (H) 178 degree (V)	178 degree (H) 178 degree (V)	178 degree (H) 178 degree (V)
	Response Time (G-t-G)		8	8	8
	Backlight Life (hrs)		30.000	30.000	30.000
	Panel Surface		AG, Haze 25%	AG, Haze 25%	AG, Haze 28%
	Operating Hour		18 hrs / 7 days	18 hrs / 7 days	18 hrs / 7 days
	Orientation		Landscape	Landscape	Landscape
Power	Туре		Internal	Internal	Internal
	Power Supply		100V~240V, 50-60Hz	100V~240V, 50-60Hz	100V~240V, 50-60Hz
	Power Consumption	Maximum (W/h)	400 W	450 W	550 W
		Typical (W/h)	200 W	245 W	330 W
		Standby Mode (W/h)	≤0.5 W	≤0.5 W	≤0.5 W
	AC Power Switch		1	I	I
	Wake up		VGA / HDMI / LAN	VGA / HDMI / LAN	VGA / HDMI / LAN
Environment	Operation Temperature		0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C
	Operating Humidity		10% ~ 90% RH Non- Condensing	10% ~ 90% RH Non- Condensing	10% ~ 90% RH Non- Condensing
Connectivity	Input	VGA	xl	×I	×I
		HDMI	2.0 ×3	2.0 ×3	2.0 ×3
	Output	HDMI	2.0 ×I	2.0 ×I	2.0 ×I
	USB	Туре А	2.0 × 3	2.0 × 3	2.0 × 3
			3.0×3	3.0×3	3.0×3
		Туре В	× 2	× 2	× 2
	RS232		Yes	Yes	Yes
	RJ45		Yes	Yes	Yes
	Remote Controller		Yes	Yes	Yes
Audio Mechanical	Internal Speaker		10W x 2	10 W × 2	16W×2
	Dimension (mm)	Screen	1450.6 × 828.1 × 90.2	1672.2 × 954.9 × 86.7	1930.8 × 1109.3 × 82.8
	Weight (kg)	Screen	26,95	33,3	54,3
		Package	40.9	49	77.1
	Bezel Width (mm)		8.8 / 12.8 / 8.8 / 8.8	9 / 13.3 / 9 / 9	13.9 / 23.4 / 13.9 / 13.9
	Wall Mounting (VESA) (Screw Type /Max. Length)		400 × 200 (4 holes); M6*10L	400 × 200 (4 holes); M8*15L	600 x 400 (4 holes); M8*20L
	OPS Slot		Yes	Yes	Yes
Model			DVY2I	DVY22	DVY23
Camera	Dimensions (H × W × D)		30 mm × 102 mm × 46 mm (1.18 in × 4.02 in × 1.81 in)	56 mm × 220 mm × 93 mm (2.20 in × 8.66 in × 3.65 in)	150 mm × 181 mm × 116 mm (5.90 in × 7.13 in × 4.55 in)
	Weight		0.15 kg (0.33 lbs)	0.53 kg (1.17 lbs)	1.38 kg (3.04 lbs)
	Sensor	Sensor		4K UHD	1080P FHD
	Resolution		1080p, 720p, SD @ 30 fps	Main stream : 4K, 1080p, 900p, 720p @ 30 fps / Sub stream : 720p, 480p, 172p @30 fps	1080p, 720p, SD @ 30 fps
	Field of view		Horizontal: 87° Vertical: 50° Diagonal: 88°	Horizontal: 120° Vertical: 85° Diagonal: 126°	Horizontal: 55° Vertical: 31° Diagonal: 63°
	Zoom		-	Digital: 4x	Optical: 20x / Digital: 10x
	Pan Tilt		-	Digital	±170° -30° to 90°
	Pan Tilt speed		-	-	100°/sec 45°/sec
	Focus		Fixed	Auto and manual	Auto and manual
	Auto framing		-	Yes	-
	Preset positions		-	10	Remote: 10 / LAN: 255
	Lens type		Glass	Glass	Glass
	Low light performance		0.5 Lux	0.1 Lux	0.5 Lux
	0 1 1 1 1 1 1				