

Features

X-Sign Content Management Software

BenQ's intergrated, exclusive X-Sign software provides content templates that are especially designed for long-and-narrow displays, making it easy for operators to quickly design and roll out new promotional material. The templates also let operators add images, videos, and scrolling text to their marketing materials. X-Sign's intuitive interface makes it easy for operators to monitor and manage all remote displays from a central, off-site location. It allows operators to push real time massages, to make instant price updates and broadcast YouTube live streaming across multiple displays. The software has QR Code Interaction and Analysis option. X-Sign allows operators to embed QR Codes that, when scanned, can offer customers the latest promotional information. X-Sign also offers QR Code analysis to let operators see when and where customers are interacting with content. This analysis can help operators quickly adjust their offers to match customer interest.

Performance

As the world's first PANTONE validated digital signage, BenQ SL5502K aims to provide users the most professional colour performance to fulfill their daily tasks, including design, display and other related display applications. An ultra-high definition resolution of 4K2K (3840 × 2160) offers the most exquisite image details and allows for flexible colour adjustment to display captivating images. SL5502K is built with better cooling techniques reaching a longer lifetime while running for 24 hours a day and delivers flawless display in portrait and landscape view.

Intuitive Design

A slim and lightweight design combines with a narrow bezel delivers a stylish outlook befitting of any in-store environment. It can easily be mounted or rearranged to suit diverse uses, which saves cost and manpower on signage installation, and eventually facilitates different display configurations in stores, offices, and other commercial establishments.

Hassle-free Display Management

With Device Management Solution operators can remotely control display on/off time or backlight via LAN. Over-the-Air Update allows to keep all display drivers up-to-date with easy firmware update. DMS Cloud gives operators control of all devices in the store and lets them install AndroidTM apps and distribute content via cloud server.

All-in-One, Clutter Free Solution

BenQ's Smart Signage Series is an all-in-one media solution with a built-in Android operating system. It allows users to work as soon as it's plugged in. Plug-and-play simplicity enables you to access and play multimedia files directly from a USB flash drive. Requires no PC connection or complicated cable setup.

Input and Output Terminals









Specifications			
Panel	Screen Size Resolution Brightness (Typ.) Contrast Ratio (Typ.) Viewing Angle (H/V) Response Time (G-t-G) Backlight Life (hrs) Panel Surface Operating Hours		55'' 3840 x 2160 500 nits 1200 : 1 178 / 178 8 ms 50,000 Anti-Glare 24 / 7
Power	Orientation Type Power Supply Power Consumption	Maximum (W/h) Typical (W/h) Standby Mode (W/h) Off Mode (W/h)	Landscape / Portrait Internal 100 V~240 V, 50 Hz / 60 Hz 148 W 85.6 W <0.5 W 0 W
Environment	AC Power Switch Wake up Operation Temperature		Yes HDMI / VGA / DP 0°C ~ 40°C
Connectivity	Operating Humidity Input Output	VGA HDMI Display Port Audio Input HDMI Audio Output	20% ~ 80% RH non-condensing x HDMI 2.0 x 2 DP 1.2 x x (3.5 mm) HDMI 2.0 x x (3.5 mm)
	USB RS232 RJ45 Remote Controller		USB 3.0×2 / USB 2.0×2 Yes Yes
Audio	Internal Speaker		$10W \times 2$
Mechanical	Dimensions (mm) Weight (kg)	Screen Package Screen Package	1236.4 × 707.2 × 63.1 1364 × 824 × 154 26.4 31.4
	Bezel Width (mm) Wall Mounting (VESA) (Screw Type /Ma:	x. Length)	11.8 400 x 400 mm M6 x 14 mm

Dimension (mm)





BenQ Europe B.V.

Meerenakkerweg I-17 5652 AR Eindhoven The Netherlands Tel: +31 88 8889200

region, please visit your local stores for details. Actual product's features and specifications are may include corporate names and trademarks of third parties which are the properties of the third parties respectively.



Unit: mm

