

Features

X-Sign Content Management Software

BenQ's intergrated, exclusive X-Sign software provides content templates that are especially designed for long-and-narrow displays, making it easy for operators to quickly design and roll out new promotional material. The templates also let operators add images, videos, and scrolling text to their marketing materials. X-Sign's intuitive interface makes it easy for operators to monitor and manage all remote displays from a central, off-site location. It allows operators to push real time massages, to make instant price updates and broadcast YouTube live streaming across multiple displays. The software has QR Code Interaction and Analysis option. X-Sign allows operators to embed QR Codes that, when scanned, can offer customers the latest promotional information. X-Sign also offers QR Code analysis to let operators see when and where customers are interacting with content. This analysis can help operators quickly adjust their offers to match customer interest.

Performance

As the world's first PANTONE validated digital signage, BenQ SL6502K aims to provide users the most professional colour performance to fulfill their daily tasks, including design, display and other related display applications. An ultra-high definition resolution of 4K2K (3840 × 2160) offers the most exquisite image details and allows for flexible colour adjustment to display captivating images. SL6502K is built with better cooling techniques reaching a longer lifetime while running for 24 hours a day and delivers flawless display in portrait and landscape view.

Intuitive Design

A slim and lightweight design combines with a narrow bezel delivers a stylish outlook befitting of any in-store environment. It can easily be mounted or rearranged to suit diverse uses, which saves cost and manpower on signage installation, and eventually facilitates different display configurations in stores, offices, and other commercial establishments.

Hassle-free Display Management

With Device Management Solution operators can remotely control display on/off time or backlight via LAN. Over-the-Air Update allows to keep all display drivers up-to-date with easy firmware update. DMS Cloud gives operators control of all devices in the store and lets them install AndroidTM apps and distribute content via cloud server.

All-in-One, Clutter Free Solution

BenQ's Smart Signage Series is an all-in-one media solution with a built-in Android operating system. It allows users to work as soon as it's plugged in. Plug-and-play simplicity enables you to access and play multimedia files directly from a USB flash drive. Requires no PC connection or complicated cable setup.

Input and Output Terminals








Specifications			
Panel	Screen Size		65"
	Resolution		3840 × 2160
	Brightness (Typ.)		500
	Contrast Ratio (Typ.)		1200 : 1
	Viewing Angle (H/V)		178 / 178
	Response Time (G-t-G)		8 ms
	Backlight Life (hrs)		50,000
	Panel Surface		Anti-Glare
	Operating Hours		24 / 7
	Orientation		Landscape / Portrait
Power	Туре		Internal
	Power Supply		100 V~240 V, 50 Hz / 60 Hz
	Power Consumption	Maximum (W/h)	270W
		Typical (W/h)	225W
		Standby Mode (W/h)	≤0.5W
		Off Mode (W/h)	0₩
	AC Power Switch		Yes
	Wake up		HDMI/VGA/DP
Environment	Operation Temperature		0°C ~ 40°C
	Operating Humidity		20% ~ 80% RH non-condensing
Connectivity	Input	VGA	× I
		HDMI	HDMI 2.0 × 2
		Display Port	DP 1.2 x 1
		Audio Input	x I (3.5 mm)
		Audio Output	x I (3.5 mm)
	USB		USB 3.0 × 2 / USB 2.0 × 2
	RS232		Yes
	RJ45		Yes
	Remote Controller		Yes
Audio	Internal Speaker		10W × 2
Mechanical	Dimensions (mm)	Screen	1454.6 × 829.6 × 72.0
		Package	1660 × 1045 × 245
	Weight (kg)	Screen	35,5
		Package	48
	Bezel Width (mm)		12,6
	Wall Mounting (VESA) (Screw Type /Ma	x. Length)	400 × 400 mm M8 × 20L

Dimension (mm)





BenQ Europe B.V.

Meerenakkerweg I-17 5652 AR Eindhoven The Netherlands Tel: +31 88 8889200

business-display.benq.eu

© 2019 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.



Unit: mm