



Model **ds55LX3**

55" High Brightness 1500 nit LCD with Super Narrow Bezel

The DS55LX3 combines the benefits of a high bright display with a super narrow bezel for tiled video wall applications. This model features a full HD 55-inch IPS LCD with a high brightness backlight producing a 1,500 nit image. Each screen comes individually color calibrated for exceptional color quality and uniformity amongst multiple displays. With an ultra slim 5.3 mm bezel-to-bezel width, multiple screens can be placed side by side to create near seamless image.

Key Features

- Super narrow bezel for video wall applications
- High brightness 1,500 cd/m²
- IPS panel for superior color uniformity
- D65 color calibrated
- Built-in video wall daisy-chaining
- Low power consumption
- Full HD 1080p resolution
- Direct LED backlit with local dimming
- *EvenGlow* uniform backlighting prevents hot spots
- Blackening defect-free up to 110°C (230°F)
- Portrait and landscape orientation
- Durable all metal construction

Screen image simulated.

55" High Brightness 1500 nit LCD with Super Narrow Bezel

Model **ds55LX3**

PANEL

LCD Panel Type	54.6 inches color IPS LCD
Native Resolution	1920 x 1080
Backlight	Direct LED
Brightness	1500 cd/m ² (typ)
Default Color Temperature	D65 (6500 k)
Contrast Ratio	3,000:1 (static) 1,000,000:1 (dyn)
Response Time	10 ms (typ)
Viewing Angle	178° / 178°
Light Life Time	50,000 hrs (typ)
Blackening Defect Free	Up to 110°C (230°F)
Panel Surface	AG Haze 10%, 3H

POWER

Power Supply	Internal
Rated Voltage	100 V ~ 240 V, 50 Hz / 60 Hz
Power On Mode	195 W (typ), 300 W (max)
Power Saving Mode	< 1 W
AC Out	< 100 W

MECHANICAL SPECS

Bezel Width (T/B/L/R)	3.40 / 1.90 / 3.45 / 1.85 mm
Cabinet Color	Black
Monitor Dimension (LxHxD, w/o stand)	1215.2 x 686 x 121 mm
Monitor Weight (set/package)	36 kg / 40 kg
VESA Mounting (dimension)	400 x 400 mm / 800 x 400 mm
Orientation	Portrait / Landscape

USER INTERFACE

Image Setting	Yes
Source/Volume Control	Optional with A-D Converter Box
Language	English
Daisy Chain	DVI, RS-232
Sharpness Enhancement	Yes
Proof of Image Retention	Yes
Dimming Control (DCR)	Yes
Picture in Picture (PIP)	Optional with A-D Converter Box
De-interlacing/Comb Filter	Optional with A-D Converter Box
Built-in Video Wall Support	Up to 6x6
ID Setting for Daisy Chain	Yes
On/Off Scheduling	Yes
Ambient Light Sensor	Yes
Total Turn-on time	Yes
Internal Temperature Sensor	Yes
Network Control	RS-232, RS-485 (RJ45)
OSD Menu Rotation	Yes

VIDEO INPUT

DVI-D	x1
HDMI	Optional with A-D Converter Box
VGA	Optional with A-D Converter Box
Component	Optional with A-D Converter Box
S-Video	Optional with A-D Converter Box
Composite	Optional with A-D Converter Box

ACCESSORIES

Remote Control	Yes
Users Guide / Driver CD-ROM	Yes
Video Cable	DVI
Power Cable	Yes






ENVIRONMENT

Operating Temperature	0° C ~ 40° C
Storage Temperature	-20° C ~ 60° C
Humidity	10% ~ 80% RH Non-Condensing

CERTIFICATION

CE / FCC / ROHS

All specifications are subject to change without notice.



121 mm / 4.8"

DynaScan Technology, Inc.
7 Chrysler, Irvine, CA 92618, USA
Tel: +1 949-421-0348, +1 866-508-4848
Email: info@dynascanusa.com