



COMMERCIAL DISPLAY

CDE4302

Key Features

- USB multimedia player
- vController software
- Hospitality mode
- Supports HDMI CEC pass-through
- Flicker-free and Blue Light Filter eye-care technologies



Product Description

The ViewSonic CDE4302 is a 43" Full HD direct-lit LED commercial display, offering the combination of cost-efficiency and ease of installation for corporate, retail and hospitality environments. With an integrated media player, the CDE4302 is able to easily playback high definition messaging via your USB port. Versatile connectivity options include 2 HDMI ports, VGA, RS232 and SPDIF. The display provides an easy one-time installation and is compatible with many different devices. With Full HD resolution, 350-nit brightness, and wide viewing angles, the slim-bezel CDE4302 delivers sharp and vivid images to ensure smooth content playback. This display also supports HDMI CEC pass-through for one-touch-play and an RS232 control port with IR pass-through for easy installation. The display is also equipped with exclusive eye-care technologies, including Flicker-Free and Blue Light Filter, creating a more comfortable viewing experience. Free-bundled vController software offers easy maintenance and an intuitive interface for remote management via a PC server or laptop.

Visit Us ■ www.viewsonic.com

LCD PANEL

Panel Size:	43"
Type/ Tech:	TFT LCD Module. (VA type, DLED backlight)
Display Area (mm):	940.9(H) x 529.25 (V) (43" diagonal)
Aspect Ratio:	16:9
Resolution:	1920x1080
Colours:	16.7M colours
Brightness:	350 nits (typ.)
Contrast Ratio:	3000:1 (typ.)
Response Time:	6.5 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	DLED
Backlight Life:	30,000 Hours (typ.)
Surface Treatment:	Anti-Glare, 3H, Haze 2% (typ)

TOUCH

INPUT

HDMI:	x2 (1.4)
RGB / VGA:	x1
Audio:	x1 (3.5mm jack)
RS232:	x1

OUTPUT

Audio:	x1 (Earphone out) (3.5mm jack)
SPDIF:	x1

LAN

USB

Type A:	x1 (2.0)
---------	----------

SPEAKERS

10W x2

BUILT-IN PC

COMPATIBILITY

RGB PC/HDMI PC:	480i, 480p,720p,1080i,1080p
HDMI:	480i, 480p,720p,1080i,1080p

CONTROLS

Physical- Top OSD:	POWER, MUTE, INPUT, VOL -/+, UP, DOWN, MENU PICTURE: Auto Picture, Brightness, Contrast, Colour, Advanced settings, Reset picture setting SOUND: Auto sound, Equalizer, Balance, Reset sound settings CLOCK: Sleep timer, Date/Time. FEATURES: Language, PC settings, Button lock, Remote lock, Monitor ID, Current software info, Reset AV & features USB MENU: Photo, Music, Movie
--------------------	--

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	"On" 105W "Off" (Suspend) < 0.5 W

ERGONOMICS

Wall Mount (VESA®):	200x200mm / 400x400mm ; Screw: M6*10mm
----------------------	--

OPERATING CONDITIONS

Temperature (° C):	0°C to 40°C (Landscape)
Humidity:	20% ~ 80% non-condensing

DIMENSIONS

(W X H X D)

Physical (inch / mm):	968.2 x 559.4 x 59.9 mm / 38.12 x 22.02 x 2.36 in.
Packaging (inch / mm):	1070 x 696 x159 mm / 42.13 x 27.40 x 6.26 in

WEIGHT

Net (lb / kg):	8.70 kg / 19.18 lbs
Gross (lb / kg):	12.20 kg / 26.90 lbs

REGULATIONS

Standard:	CE, CB, ErP, WEEE, C-tick, cTUVus, FCC, Energy Star 7.1, Mexico Energy, EPEAT
-----------	---

WARRANTY

**Warrant offered may differ from market to market
--

WHAT'S IN THE BOX?

1. CDE4302 commercial display 2. Remote Control with batteries 3. User manual CD wizard 4. Quick Start Guide 5. Power Cables 6. VGA cable 7. RS232
*Actual content may differ from market to market