

Key Features

- WQHD 1440p resolution
- SuperClear® IPS technology
- 10-bit colour
- Narrow bezel
- HDMI and DisplayPort inputs



Product Description

The ViewSonic® VG2719-2K is a versatile 27" WQHD monitor with rich and accurate color performance for the office. Whether doing graphic design or just general office work, VG2719-2K is sure to rise to the occasion. Featuring a WQHD resolution panel (2560 x 1440) and SuperClear® IPS-Type technology, content is displayed in sharp detail from virtually any viewing angle. WQHD resolution also means that more displayable content can be displayed on the screen than Full HD, making multitasking more manageable and boosting productivity. VG2719-2K comes equipped with 10-bit color which can produce 1.07 billion colors and makes color transitions seamless. VG2719-2K's edge-to-edge frameless gives the monitor a clean aesthetic and is convenient for setting up multiple monitors side-by-side to improve workflow management without the distraction of a bulky bezel.



1. VESA Compatible (Wall Mount 100 x 100mm)
2. AC In
3. Display Port
4. Earphone
5. Audio In
6. HDMI x 2

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	300 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 76% size (Typ) sRGB: 107% size / 99% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

3.5mm Audio In:	1
3.5mm Audio Out:	1
HDMI 1.4:	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	21W
Eco Mode (optimized):	27W
Consumption (typical):	33W
Consumption (max):	35W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	1, 2, Up, Down, Power
On Screen Display:	Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 120KHz
Frequency Vertical:	24 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
---------------	------------------------------------------------

ERGONOMICS

Height Adjust (mm):	110
Swivel:	320°
Tilt (Forward/Back):	-5° / 22°
Pivot (Right/Left):	91° / 0°

WEIGHT (IMPERIAL)

Net (lbs):	15
Net Without Stand (lbs):	9.9
Gross (lbs):	18.7

WEIGHT (METRIC)

Net (kg):	6.8
Net Without Stand (kg):	4.5
Gross (kg):	8.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	28.5 x 17.5 x 7.5
Physical (in.):	24.4 x 16.68~21.01 x 9.6
Physical Without Stand (in.):	24.4 x 14.3 x 1.8

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	725 x 444 x 190
Physical (mm):	620 x 423.7~533.7 x 245
Physical Without Stand (mm):	620 x 362 x 45

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, GS, UKCA, VCCI, PSE, KC/KCC, e-Standby
PACKAGE CONTENTS:	VG2719-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Audio Cable (Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market