

# ViewSonic® LED DISPLAY VG2748

## Key Features

- vDisplay Manager (free download)
- Narrow bezel
- HDMI, DisplayPort and VGA inputs
- SuperClear® IPS technology
- Versatile stand design



## Product Description

ViewSonic VG2748 is a 27" (27" viewable) 1080p monitor with productivity enhancing features including IPS technology and an advanced ergonomic design for the modern day office. Utilising SuperClear® IPS panel technology and 1080p resolution, VG2748 delivers crisp, clear images from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2748 uses environmentally friendly packaging and offers quick and easy out-of-the-box set-up via the quick release stand. The cloud client mount on the back of the monitor stand coupled with cable management design features, makes VG2748 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0 inputs.



1. VESA Compatible(Wall mount 100mm x 100mm)
2. Menu Control Panel
3. USB down stream x 2
4. AC In
5. DisplayPort
6. HDMI
7. VGA
8. USB up stream
9. USB down stream x 2

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Monitor Size:	27"W (27" Viewable) LCD monitor
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	597.9(H) x 336.3(V) mm
Aspect Ratio:	16:9
Brightness:	300 cd/m2 (Typ.)
Contrast Ratio:	1000:1 (Typ.)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	178 degrees (Typ.) / 178 degrees (Typ.)
Response Time:	GTG: 5ms (Typ.)
Pixel Size:	0.311 (H) x 0.311 (V) mm

**INPUT SIGNAL**

Frequency:	Analog: Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz Digital: Fh = 24 ~ 82KHz ; Fv = 24 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green / TMD5 / PCI-E

**COMPATIBILITY**

PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®:	Power Mac tested

**CONNECTOR**

Input:	VGA x 1, HDMI x 1 (v1.4 compatible), DisplayPort 1.2 x 1
--------	--

**AUDIO**

Speaker:	2W x 2
----------	--------

**USB**

Upstream:	USB 3.0 Type B x 1
Downstream:	USB 3.0 Type A x 4

**POWER**

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	29.15W
Optimize:	23.06W
Conserve:	18.50W

**ERGONOMICS**

Tilt:	40 ~ -5 degrees
Swivel:	+/-60 degrees
Pivot:	+/-90 degrees
Height Adjust:	0~130 mm

**SPECIAL FEATURES**

Eye Care:	Blue light filter, Flicker Free
-----------	------------------------------------

**WALL MOUNT**

VESA®:	100mm x 100mm
--------	---------------

**OPERATING CONDITIONS**

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS (W X H X D) (MM)**

Physical with stand (mm):	620.7mm (W) x 537.2mm (H) x 202.2 mm (D)
Physical without stand (mm):	620.7 mm (W) x 366.1mm (H) x 51.1 mm (D)
Packaging (mm):	692 mm (W) x 430 mm (H) x 218 mm (D)

**WEIGHT**

Net with stand:	7.3kg
Net without stand:	4.9kg
Gross:	10.1 kg

**REGULATIONS**

CTUVus, FCC-B, ICES003, Energy Star , EPEAT, TUV  
Mexico CoC, Mexico Energy, CE, CB , RoHS , Erp,  
REACH SVHC, EEL , WEEE, TCO, GS, EAC/CU,  
UkrSEPRO

**PACKAGE CONTENTS**

LCD Display  
Power Cable (1.8m)  
DP to DP Cable (1.8m)  
USB3.0 Upstream Cable (1.8m)  
Quick Start Guide