

ViewSonic®  LED DISPLAY
VP2768


Key Features

- Hardware colour calibration
- Frameless bezel
- Ergonomic stand with auto pivot
- Delta E < 2 colour accuracy
- Pre-calibrated uniformity correction



Product Description

Engineered to deliver unmatched colour accuracy crucial for professional applications, the ViewSonic® VP2768 WQHD monitor displays your work with the vivid and lifelike colour it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP2768 provides a near-seamless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2768 is equipped with future-proof DisplayPort technology, in addition to HDMI. To ensure precise, uniform colour, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior colour accuracy. An integrated colour uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colours. Add to that 6-axis colour adjustment functionality, and this monitor provides the ultimate colour processing capability for professional applications. What's more, an advanced ergonomic design delivers customized comfort for increased productivity. Hardware calibration function is also available which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other colour-critical applications.



Visit Us ■ www.viewsonic.com

DISPLAY

| | |
|-------------------------|--|
| Monitor Size: | 27"W |
| Panel Technology: | IPS TFT LCD |
| Resolution: | WQHD 2560 x 1440 |
| Display Area: | 596.74mm (H) x 335.66mm (V) |
| Aspect Ratio: | 16:9 |
| Brightness: | 350 cd/m2 (Typ) |
| Contrast Ratio: | 1000:1 (Typ) |
| Dynamic Contrast Ratio: | 20,000,000:1 |
| Viewing Angle: | 178 degrees / 178 degrees (Typ) |
| Response Time: | GTG(AVG): 5 m |
| Colour Gamut: | NTSC: 76.88% Coverage sRGB: 99.92% Coverage REC709: 99.98% Coverage SMPTE-C: 100% Coverage EBU: 99.98% Coverage |
| Pixel Size: | 0.2331mm (H) x 0.2331mm (V) |

INPUT SIGNAL

| | |
|------------|--|
| Frequency: | Fh = 15 ~ 90KHz ; Fv = 59 ~ 61Hz |
| Sync: | HDMI: TMDS DisplayPort/ mini DP: Mini-Packet |

COMPATIBILITY

| | |
|-------|---|
| PC: | PC Compatibles (2560 x 1440 HDMI/DisplayPort Non-Interlaced) |
| Mac@: | Power Mac (up to 2560 x1440 HDMI/DisplayPort) |

CONNECTOR

| | |
|------------|---|
| Digital: | DisplayPort 1.2a DisplayPort Out (Support DaisyChain) Mini DP 1.2a HDMI 1.4 x 2 |
| Audio Out: | 3.5mm Audio out (Earphone) x 1 |

USB

| |
|---|
| USB3.0 upstream x1 USB3.0 downstream x 4 |
|---|

POWER

| | |
|--------------|-------------------------------------|
| Power: | 3-pin plug (CEE22) x 1 |
| Voltage: | AC 100-240V (Universal); 50/60Hz |
| Consumption: | 32W |
| Optimize: | 26.5W |
| Conserve: | 22.5W |

MODEL COLOUR

| |
|-------|
| Black |
|-------|

ERGONOMICS

| | |
|--------------------|---|
| Tilt: | -5.0° ~ 21.0° |
| Swivel: | 120° |
| Pivot: | 0~90 degree (Clockwise and Counter Clockwise) |
| Height Adjustment: | 0~130mm |

SPECIAL FEATURES

| |
|--|
| Eye-care, Auto pivot, Support hardware calibration |
|--|

WALL MOUNT

| | |
|--------|---------------|
| VESA®: | 100mm x 100mm |
|--------|---------------|

OPERATING CONDITIONS

| | |
|--------------------------|---------------------------------|
| Temperature (° F / ° C): | 32°F to 104°F (0°C to 40°C) |
| Humidity: | 20% to 90% (no condensation) |

DIMENSIONS (W X H X D) (MM)

| | |
|------------------------------|---|
| Physical with stand (mm): | 613 mm (W) x 540 mm (H) x 215 mm (D) |
| Physical without stand (mm): | 613 mm (W) x 353 mm (H) x 50 mm (D) |
| Packaging (mm): | 720 mm (W) x 268 mm (H) x 460 mm (D) |

WEIGHT

| | |
|-------------------------|---------|
| Net with stand (kg): | 6.88 kg |
| Net without stand (kg): | 4.39 kg |
| Gross (kg): | 9.60 kg |

REGULATIONS

| |
|--|
| cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UkrSEPRO, BSMI, RCM, KC, CCC, China RoHS, China Energy Label |
|--|

PACKAGE CONTENTS

| |
|---|
| LCD Display Power Cable (cable length :1.8M) DP Cable (mini DP to DP) (cable length :1.8M) USB 3.0 UPstream Cable (Type B to A) (cable length :1.8M) Quick Start Guide ViewSonic Wizard CD-ROM *Actual content may differ from market to market |
|---|