



LED DISPLAY

VX2776-4K-MHD

Key Features

- HDR10 content support
- SuperClear® IPS technology
- Frameless bezel and metallic triangle stand
- 10-bit colour
- Dual HDMI and DisplayPort inputs



Product Description

Whether for office use or enjoying entertainment at home, the ViewSonic® VX2776-4K-mhd is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience that's ideal for multi-monitor setups. Stunning 4K Ultra HD resolution generates 4-times more pixels than Full HD monitors, which boosts efficiency and image detail to enhance both work and play. A mega dynamic contrast ratio of 80M:1 delivers more image depth for a better user experience, while HDR10 content support results in vivid colours and brightness that exceed that of standard monitors. Built-in HDMI and DisplayPort inputs offer flexible connectivity options for a wide range of devices.

Visit Us ■ www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD
Static Contrast Ratio:	1,300:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	350 cd/m2 (typ)
Colours:	1.07B
Colour Space Support:	10 bit (8 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Response Time (GTG w/OD):	3.8ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Colour Gamut:	NTSC: 72% size (Typ) sRGB: 110% size (Typ)
Pixel Size:	0.155 mm (H) x 0.155 mm (V)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
Display Port:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2.5Watts x2
--------------------	-------------

POWER

Eco Mode (Conserve):	33W
Eco Mode (optimised):	38W
Consumption (typical):	43W
Consumption (max):	44W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.5W
Power Supply:	Internal

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 160KHz
Frequency Vertical:	40 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-3° / 20°
----------------------	-----------

WEIGHT (METRIC)

Net (kg):	5.6
Net Without Stand (kg):	5
Gross (kg):	7

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	697 x 462 x 132
Physical (mm):	616 x 451 x 184
Physical Without Stand (mm):	616 x 366 x 46

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star 8.0, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
--------------	--

PACKAGE CONTENTS:	VX2776-4K-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, Quick Start Guide x1
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--