



LED DISPLAY

VX3211-4K-mhd

Key Features

- 95% NTSC wide colour gamut coverage
- AMD FreeSync™ technology
- HDR10 content support
- Picture-in-Picture
- 80M:1 dynamic contrast ratio



Product Description

Whether for office use or for enjoying entertainment at home, the VX3211-4K-mhd is designed to take your viewing experience to another level. VX3211-4K's Ultra HD resolution is 4x higher than Full HD, which maximises efficiency and image detail due to increased coverage areas. The VX3211-4K-mhd's wide colour gamut achieves 95% of NTSC colour coverage, meaning colours can be displayed more accurately. AMD FreeSync™ virtually eliminates screen tearing and stuttering for a fluid gaming experience. A mega dynamic contrast ratio of 80M:1 gives images more depth and the user experience is enhanced in all facets of monitor usage. Built in Picture-in-Picture (PIP) mode lets you combine more content at the same time to increase efficiency. Moreover, HDR 10 can display specific levels of colour and brightness that exceed standard monitors, while built-in HDMI inputs and DisplayPort can support a wide range of devices to offer flexibility for your connection needs. *This monitor is GeForce Driver G-Sync Enable-Ready [Disclaimer].



1. VESA compatible (Wall Mount 100 x 100 mm)
2. Menu Control Panel
3. AC Power in
4. HDMI x 2
5. DisplayPort
6. Earphone Out
7. Internal Speakers

Visit Us www.viewsonic.com

DISPLAY

Monitor Size:	32"W (31.5" Viewable)
Panel Technology:	VA TFT LCD
Resolution:	UHD 3840 x 2160
Display Area:	698.4mm (H) x 392.85mm (V)
Aspect Ratio:	16:9
Brightness:	300 cd/m2 (Typ)
Contrast Ratio:	3000:1 (Typ)
Dynamic Contrast Ratio:	80,000,000:1
Viewing Angles:	178 degrees / 178 degrees (Typ)
Colours:	1.07 Billion colors (8- bit+Hi-FRC)
Colour Gamut:	95% of NTSC

INPUT SIGNAL

Frequency:	HDMI: Fh = 15 ~ 204KHz ; Fv = 40 ~ 60Hz, DisplayPort: Fh = 135 ~ 135KHz ; Fv = 40 ~ 60Hz
Sync:	TMD5, PCI-E

COMPATIBILITY

PC:	Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Input:	HDMI x 2 (v2.0 compatible), DisplayPort x 1 (v1.2 compatible)
Output:	Earphone out x 1 (3.5mm plug)

AUDIO

Speaker:	2.5W x 2
----------	----------

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz

ERGONOMICS

Tilt:	13 ~ -5 degrees
-------	-----------------

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	729.7mm (W) x 495.5mm (H) x 230.31mm (D)
Physical without stand (mm):	729.7mm (W) x 432.8mm (H) x 64.32mm (D)
Packaging (mm):	838mm (W) x 615mm (H) x 282mm (D)

REGULATIONS

VSE:	cTUVus, FCC-B, ICES003, GEC, MX- CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, VCCI, PSE, KC, e-Standby, CCC, China RoHS, China Energy Label
------	--

PACKAGE CONTENTS

LCD Display, Power Cable (1.5m), HDMI Cable (1.5m), Quick Start Guide
