



LED DISPLAY

# VX3276-2K-mhd

## Key Features

- SuperClear® IPS technology
- Frameless bezel and metallic triangle stand
- 10-bit colour
- HDMI, DisplayPort and mini DP inputs
- Dual integrated speakers



## Product Description

The ViewSonic VX3276-2K-mhd is the perfect blend of style and performance with features that include a sizeable 32" panel, a minimalist design, and WQHD (2560 x 1440) resolution. The sleek design of an ultra-slim profile, metallic silver triangle stand, and a sleek edge-to-edge frameless bezel give the monitor a premium feel that fits nicely both at home and in the office. VX3276-2K-mhd features SuperClear® IPS technology and rich 10-bit colour to produce an extensive array of vibrant colours with wide viewing angles. Stereo sound is provided by the monitor's dual integrated speakers, while DisplayPort, Mini DisplayPort, and 2 HDMI ports offer flexible connectivity options for both general usage and gaming.

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Monitor Size:	32"W (31.5" Viewable)
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	2560 x 1440
Display Area:	698.11mm (H) x 392.68mm (V)
Aspect Ratio:	16:9
Brightness:	250 cd/m2 (Typ)
Contrast Ratio:	1200:1 (Typ)
Dynamic Contrast Ratio:	80,000,000:1
Viewing Angle:	178 degrees / 178 degrees (Typ)
Response Time:	4ms (GtG)
Colours:	1.07 Billion colours (10 bits colour depth)
Colour Gamut:	75% of NTSC (Typ)
Panel Surface:	Anti-Glare type, Hard-coating (3H), Haze 25%
Pixel Pitch:	0.273mm (H) x 0.273mm (V)

**INPUT SIGNAL**

Frequency:	HDMI:Fh = 15 ~ 113KHz ; Fv = 24 ~ 75Hz DisplayPort:Fh = 24 ~ 113KHz ; Fv = 50 ~ 75Hz Mini DP:Fh = 24 ~ 113KHz ; Fv = 50 ~ 75Hz
Sync:	HDMI:TMDS DisplayPort:PCI-E Mini DP:PCI-E

**COMPATIBILITY**

PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®:	Power Mac tested

**CONNECTOR**

Digital:	HDMI x 2 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible) Mini DisplayPort x 1 (v1.2 compatible)
Audio Out:	Earphone out x 1 (3.5mm plug)

**SPEAKERS**

2W x 2
--------

**POWER**

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	43W
Optimize:	41W
Conserve:	36W

**ERGONOMICS**

Tilt:	15 ~ -4 degrees
-------	-----------------

**SPECIAL FEATURES**

DDC/2B, DDC/CI, HDCP, Detachable Base, KENSINGTON Microsaver Security Compatible

**WALL MOUNT**

VESA®:	100mm x 100mm
--------	---------------

**OPERATING CONDITIONS**

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS (W X H X D) (MM)**

Physical with stand (mm):	712.89mm (W) x 503.87mm (H) x 230mm (D)
Physical without stand (mm):	712.89mm (W) x 416.4mm (H) x 38.2mm (D)
Packaging (mm):	785mm (W) x 498mm (H) x 112mm (D)

**WEIGHT**

Net with stand (kg):	6.2kg
Net without stand (kg):	5.6kg
Gross (kg):	8.2kg

**REGULATIONS**

cTUVus, FCC-B, ICES003, Energy Star 8.0, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, KC, e-Standby, BIS

**PACKAGE CONTENTS**

LCD Display  
Power Cable  
HDMI Cable  
Quick Start Guide  
\*Actual content may differ from market to market