



LED DISPLAY

VX3276-mhd-2

Key Features

- SuperClear® IPS technology
- Frameless bezel and metallic triangle stand
- Full HD 1080p resolution
- Flicker-Free and Blue Light Filter
- HDMI, DisplayPort and VGA inputs



Product Description

The ViewSonic VX3276-mhd-2 is the perfect blend of style and performance with features that include a sizeable 32" (31.5" viewable) panel, a minimalist design, metallic silver triangle stand, and a sleek edge-to-edge frameless bezel give the monitor a premium feel that fits nicely both at home and in the office. VX3276-mhd-2 features 1080p resolution, SuperClear® IPS technology and dual integrated speakers to produce astonishing visual and sound effect from multimedia contents.

Visit Us — www.viewsonic.com

DISPLAY

Monitor Size:	32"W (31.5" Viewable)
Panel Technology:	SuperClear® IPS TFT CD
Resolution:	1920 x 1080
Display Area:	698.4mm (H) x 392.85mm (V)
Aspect Ratio:	16:9
Brightness:	250 cd/m2 (Typ)
Contrast Ratio:	1200:1 (Typ)
Dynamic Contrast Ratio:	80,000,000:1
Viewing Angle:	178 degrees / 178 degrees (Typ)
Response Time:	4 ms (GtG)
Colour Gamut:	75% of NTSC (Typ)
Panel Surface:	Anti-Glare (semi-glossy) type, Haze 1%
Pixel Pitch:	0.364mm (H) x 0.364mm (V)

INPUT SIGNAL

Frequency:	VGA: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz HDMI: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz DisplayPort: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz
Sync:	VGA: Separate Sync HDMI: TMDS DisplayPort: PCI-E

COMPATIBILITY

PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Digital:	HDMI x 1 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible)
Analog:	VGA x 1
Audio Out:	Earphone out x 1 (3.5mm plug)
Audio In:	Audio in x 1 (3.5mm plug)

SPEAKERS

2W x 2

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	36W
Optimize:	31W
Conserve:	26W

ERGONOMICS

Tilt:	15 ~ -4 degrees
-------	-----------------

SPECIAL FEATURES

DDC/2B, DDC/CI, HDCP, Detachable Base, KENSINGTON Microsaver Security Compatible

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	712.89mm (W) x 503.87mm (H) x 230mm (D)
Physical without stand (mm):	712.89mm (W) x 416.4mm (H) x 38.2mm (D)
Packaging (mm):	785mm (W) x 498mm (H) x 112mm (D)

WEIGHT

Net with stand (kg):	6.2kg
Net without stand (kg):	5.6kg
Gross (kg):	8.2kg

REGULATIONS

CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, KC, e-Standby

PACKAGE CONTENTS

LCD Display
Power Cable
HDMI Cable
Quick Start Guide
*Actual content may differ from market to market