

Key Features

Higher Brightness. Longer Lamp Life.

- Auto Power Off
- 22,000:1 contrast ratio
- SuperColor™ Technology
- 5 colour modes
- · Vertical Keystone



Product **Description**

The ViewSonic PA503S offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503S projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



- 1. Keypad
- 2. LED indicator
- 3. Lamp cover
- 4. Security lock
- 5. Zoom/Focus
- 6. Front IR 7. Projection Lens
- 8. Audio in/out 9. HDMI
- 10. Dual VGA
- 11. VGA out
- 12. Mini USB
- 13. Video
- 14. Kensington® Lock Slot

15. RS232

Visit Us - www.viewsonic.com

SPECIFICATION

SPECIFICATION			
Native Resolution:	800x600		
DC type:	DC3		
Brightness:	3800 ANSI Lumens		
Contrast Ratio with SuperEco mode:	22000:1		
Display Colour:	1.07 Billion Colours		
Light Source:	Lamp		
Light source life (Nor/SuperEco):	5000/15000		
Lamp Watt:	190W		
Lens:	F=2.56-2.68, f=22-24.1 mm		
Projection Offset:	120%+/-5%		
Throw Ratio:	1.96~2.15		
Image size:	30" - 300"		
Throw Distance:	1.19m-13.11m(100" @3.98m)		
Keystone:	±40° (Vertical)		
Optical Zoom:	1.1x		
Audible Noise (Eco):	27dB		
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (D-SUB 15 pin):	2		
Composite:	1		
Audio-in (3.5mm):	1		
HDMI:	1 (Back)		
ОЦТРИТ			
Monitor out (D-SUB 15 pin):	1		
Audio out (3.5mm):	1		
Speaker:	2W		
CONTROL			
RS232:	1		

OTHERS

	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
	Power Consumption:	Normal: 260W Standby: <0.5W
	Operating Temperature:	0~40°C
	Carton:	Brown
	Net Weight:	2.2kg
	Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
	Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
STANDARD ACCESSORY		
	Power Cord:	1
	VGA cable:	1
	Remote Control:	1
	QSG & CD:	QSG: 1 / CD: NA
	Air Filter:	RSPL

USB type mini B (Services):