



# PROJECTOR PG603W


## Key Features

- 22,000:1 contrast ratio
- Integrated USB reader
- Screen mirroring for smart devices via USB
- LAN/WiFi display with vPresenter Pro
- Horizontal and Vertical keystone



## Product Description

The ViewSonic PG603W projector features WXGA resolution and a brightness output of 3600 ANSI Lumens for projecting clear, detailed images in brightly lit environments. PG603W has wireless sharing capabilities and allows you to share content from laptops and other smart devices from anywhere in the room via the projector's LAN/Wi-Fi display with vPresenter Pro app. Smart device content can also be mirrored directly to the PG603W through USB connection for a simplified way to share content. The projector's integrated USB reader allows you to plug in thumb drives through the USB port to display image files such as JPG and BMP, as well as Word, PowerPoint, and Excel files without the need for a PC. In addition, the energy-saving SuperEco mode reduces power consumption and extends lamp life to a lengthy 15,000 hours for dependable long-term projection.



1. Keypad
2. LED indicator
3. Lamp cover
4. Zoom/Focus
5. Projection Lens
6. Front IR
7. Audio in/out

8. HDMI
9. Computer in
10. Monitor out
11. Mini USB for service
12. Video
13. LAN
14. USB Reader / USB WIFI

15. RS232
16. Kensington Lock

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**SPECIFICATION**

Native Resolution:	1280x800
DC type:	DC3
Brightness:	3600lm
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	200W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	100%+/-5%
Throw Ratio:	1.55-1.70
Image size:	30" - 300"
Throw Distance:	1m-10.98m(100" @3.34m)
Keystone:	H:+/-20° , V:+/-30°
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

**INPUT**

Computer in (D-SUB 15 pin):	1
Composite:	1
Audio-in (3.5mm):	1
HDMI (HDCP):	1 (Back) (HDMI 1.4/ HDCP 1.4)

**OUTPUT**

Monitor out (D-SUB 15 pin):	1
Audio out (3.5mm):	1
Speaker:	10W
USB type A (Power):	2 (1 x reader 5V/0.5A & 1 x optional wifi dongle)

**CONTROL**

RS232:	1
RJ45:	1
USB type mini B (Services):	1

**OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 270W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.3kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

**STANDARD ACCESSORY**

Power Cord:	1
VGA cable:	1
Remote Control:	1 (w/ laser pointer)
QSG & CD:	QSG: 1 / CD: NA

**OPTIONAL ACCESSORY**

Lamp/Light Source:	RLC-109
Warranty Card:	Yes (CN Only)
Air Filter:	RSPL
Carry Bag:	PJ-CASE-008