

ViewSonic® EPOSTER EP5540T

Key Features

- 3840 x 2160 4K resolution
- Infrared 10-point touch
- Embedded media player and 16GB storage
- Expandable external media player holder
- USB multimedia playback



Product Description

The ViewSonic EP5540T is a 10-point interactive 55" all-in-one free-standing digital ePoster kiosk with a sleek, slim design. Great for grabbing attention in busy, high-traffic areas, the EP5540T comes with a scratch-proof tempered glass faceplate for added durability. Featuring 4K resolution, 178°/178° wide-angle viewing, and dual 10W stereo speakers, the EP5540T delivers customised multimedia messaging with vivid clarity. Photo and video files can be played back using the embedded Quad-core media player and 16GB of internal memory, or add your own media player using the convenient media player cradle inside the lockable security door. The signage content and display management software, as well as compatibility with ProAV control systems, make for easy management of multiple displays.

Visit Us ■ www.viewsonic.com

DISPLAY

Panel Size:	55"
Type/Tech:	TFT LCD (IPS type,DLED Backlight)
Display Area (mm):	1209.6 (H) * 680.4 (V)
Aspect Ratio:	9:16
Native Resolution:	3840 x 2160
Colors:	1.07B
Brightness:	350 nits (typ.)
Contrast Ratio:	1200:1 (typ.)
Response Time:	9 ms (typ. G to G)
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	30,000 Hours Typ.
Surface Treatment:	Anti-glare
Orientation:	Portrait

TOUCH

Type/ Tech:	IR Recognition
Touch Resolution:	32768 x 32768
Touch Point:	10 Points

STORAGE

eMMC 16GB

INPUT

HDMI:	(1.4) x2
RGB / VGA:	x1
Audio:	x1 PC audio(3.5 mm)
RS232:	x1

OUTPUT

Audio:	x1 (Earphone out)
--------	-------------------

LAN

RJ45:	x1
-------	----

USB

Type A:	x3 (2.0 x 1, 3.0 x 2)
Type B:	x1 (for touch module)

SPEAKERS

10W x 2

COMPATIBILITY

RGB PC/HDMI PC:	1920x1080 @60Hz
HDMI:	2160 x 3840 @60Hz

ANDROID VERSION

5.0.1

MULTIMEDIA

Image: JPG, BMP, PNG
Video: AVI, MPG, MPEG, DAT, MP4, TS, RM, RMVB, MKV, MOV
Audio: MP3, AAC

BUNDLE SOFTWARE

vSignage

POWER

Voltage:	100-240VAC +/- 10% Wide Range
Consumption:	Normal 117 W, Max 150 W (max.) < 0.5W (Off)

OPERATING CONDITIONS

Temperature (° C):	0°C to 40°C
Humidity:	20% ~ 80% non-condensing

DIMENSIONS (W X H X D)

Physical (inch / mm):	32.28 x 74.8 x 17.71 in/820 x 1900 x 450 mm
Packaging (inch / mm):	38.7 x 79.37 x 24.33 in/983 x 2016 x 618 mm

WEIGHT

Net (lb / kg):	154.32 lbs/70 kg
Gross (lb / kg):	187.39 lbs/85 kg

REGULATIONS

cTUVus, FCC, BSMI

PACKAGE CONTENTS

1. Power Cord
2. Remote control with battery
3. Quick Start Guide
4. User Guide CD
5. Key

*Actual content may differ from market to market