datasheet VG2719-2K



Key Features

- WQHD 1440p resolution
- SuperClear® IPS technology
- 10-bit colour
- Narrow bezel
- HDMI and DisplayPort inputs



Product **Description**

The ViewSonic® VG2719-2K is a 27" WQHD full ergonomic monitor with rich and accurate colour performance for graphic design, for office work and for home entertainment. Featuring a WQHD resolution panel (2560 x 1440) and SuperClear® IPS technology, content is displayed in refined detail from virtually any viewing angle. WQHD resolution displays more content on the screen than FHD resolution, reduces scrolling and boosts productivity. The 10-bit colour depth, which produces 1.07 billion colours, and the 99% sRGB colour coverage ensures vivid colour reproduction for web content editing, graphic design or photo editing. VG2719-2K's ergonomic design offers a wide range of tilt, swivel, pivot, and height adjustments, while narrow bezel gives the monitor a clean aesthetic and is convenient for setting up multiple monitors side-by-side to improve workflow management. In addition, with optional ViewSplit software, users can divide, organize, and customize the screen layout for better workflow efficiency.



datasheet_VG2719-2K

		datasheet_VG2719-2K	
DISPLAY		WALL MOUNT	
Monitor Size:	27"W (27" Viewable)	VESA®:	100mm x 100mm
Panel Technology:	IPS TFT LCD	OPERATING CONDITIONS	
Resolution:	WQHD 2560 x 1440	Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Display Area:	596.74mm (H) x 335.66mm (V)	Humidity:	20% to 90% (no condensation)
Aspect Ratio:	16:9	DIMENSIONS (W X H X D) (MM)	
Brightness:	300 cd/m2 (Typ)	Physical with stand (mm):	620 mm (W) x 534 mm
Contrast Ratio:	1000:1 (Typ)		(H) x 245 mm (D)
Dynamic Contrast Ratio:	50,000,000:1	Physical without stand (mm):	620 mm (W) x 362 mm (H) x 44 mm (D)
Viewing Angle:	178 degrees / 178 degrees (Typ)	Packaging (mm):	190 mm (W) x 444 mm (H) x 725 mm (D)
Response Time:	GTG: 5ms (Typ)	WEIGHT	
Colours:	1.07 Billion colors (10 bits)	Net with stand (kg):	6.91kg
Colour Gamut:	Adobe RGB: 79.15%	Net without stand (kg):	5.96kg
	Panel Coverage NTSC: 71.66% Panel	Gross (kg):	8.6kg
	Coverage sRGB: 99% Panel	REGULATIONS	
	Coverage REC 709: 99% Panel Coverage SMPTE C: 100% Panel Coverage EBU: 99% Panel Coverage	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, GS, RCM, GEMS, VCCI, PSE, KC/KCC, e- Standby, CCC, China RoHS, China Energy Label	
		PACKAGE CONTENTS	
		LCD Display Power Cable (1.5m) HDMI Cable (1.5m) Audio Cable (1.5m) Quick Start Guide	
Pixel Pitch:	0.2331mm (H) x 0.2331mm (V)		
INPUT SIGNAL			
Frequency:	Fh = 15 ~ 120KHz ; Fv = 24 ~ 75Hz	*Actual content may differ from market to market	
Sync:	TMDS / PCI-E		
COMPATIBILITY			
PC:	Windows 10 certified		
Mac®:	Power Mac tested		
CONNECTOR			
Digital:	HDMI 1.3 x 2 DisplayPort 1.2 x 1		
Audio Out:	Earphone out x 1 (3.5mm plug)		
Audio In:	Audio in x1 (3.5mm plug)		
SPEAKERS			
3W x 2			
POWER			
Power:	3-pin plug (CEE22) x 1		
Voltage:	AC 100-240V (Universal); 50/60Hz		
Consumption:	33W		
Optimize:	27W		
Conserve:	21W		
ERGONOMICS			
Tilt:	22 ~ -5 degrees		
Swivel:	320°		
Rotation:	90°		
Height Adjustment:	110 mm		

Copyright $\ensuremath{\mathbb{C}}$ ViewSonic Corporation 2000-2020. All rights reserved.