


Key Features

- SuperClear® technology
- Advanced ergonomic stand for tilt or flat
- HDMI, DisplayPort and VGA inputs
- 50M:1 dynamic contrast ratio
- Supports Windows® 7/8/10/11 and selected Linux, Chrome, and Android



Product Description

The ViewSonic TD2760 is an ideal solution for both commercial and consumer touch screen applications. With an intuitive 10-point multi-touch display and a full 1080p HD resolution, the 27-inch TD2760 delivers a versatile solution for use in the office or at home, as well as for use as an information kiosk in public areas, retail, and corporate sectors. SuperClear® technology with ultra-wide viewing angles and 50M:1 MEGA Dynamic Contrast Ratio bring greater definition and clarity to multimedia content. For added convenience, cross-platform compatibility works with operating systems such as Windows 10/11, Linux, Chrome, and Android.* Built-in connectivity options include DisplayPort, HDMI, and VGA ports along with a VESA mount design, offering additional convenience for use as a wall-mount display. Additionally, the RS232 port provides local control for other RS232 connected devices, while HDMI CEC offers local control of multiple connected devices such as HD set-top boxes, media players, and sound systems. Even more, the ergonomic stand makes it easy for the user to tilt and raise the monitor, or lay it flat for the most natural position, and create a comfortable working environment. Lastly, low power consumption with Energy Star certification saves energy costs while reducing carbon emission. *Supports Windows 7/8/10/11, the latest Linux Kernel 4.X/3.X, the latest Chrome version, and Android 6.0 & 7.0



1. Internal Speakers
2. VESA Compatible(Wall Mount 100x100mm)
3. AC In
4. DisplayPort
5. HDMI
6. VGA

7. USB Down Stream X 2
8. USB Up Stream
9. RS232
10. Earphone
11. Audio In

Visit Us

www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	6ms
Response Time (GTG w/OD):	6ms
Response Time (Typical Tr+Tf):	12ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)
Pixel Size:	0.311 mm (H) x 0.311 mm (V)
Touch Screen:	Projected Capacitive, 10-point multi-touch
Surface Treatment:	Anti-Glare, Hard Coating (≥6H)
Cover Glass Thickness:	1.88mm

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
3.5mm Audio In:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
RS232 In:	1

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	19W
Eco Mode (optimized):	22W
Consumption (typical):	26W
Consumption (max):	28W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	1, 2, Up, Down, Power
--------------------	-----------------------

On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
--------------------	---

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 90KHz
Frequency Vertical:	50 ~ 76Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Analog Sync:	Separate/Composite/SOG - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-4° / 90°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	17.4
Net Without Stand (lbs):	12.2
Gross (lbs):	22.6

WEIGHT (METRIC)

Net (kg):	7.9
Net Without Stand (kg):	5.5
Gross (kg):	10.2

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	29.6 x 20.7 x 8
Physical (in.):	26 x 17.5 x 9.4
Physical Without Stand (in.):	26 x 16.2 x 2.3

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	753 x 525 x 204
Physical (mm):	660 x 443 x 239
Physical Without Stand (mm):	660 x 410 x 58

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, RCM, GEMS, BIS, CCC, China RoHS, China Energy Label, CECP
--------------	--

PACKAGE CONTENTS:	TD2760 x1, 3-pin Plug (IEC C13 / CEE22) x1, VGA Cable (Male-Male) x1, HDMI Cable (v1.4; Male-Male) x1, Audio Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	---

Warranty:	*Warranty offered may differ from market to market
-----------	---

Power Management:	Energy Star standards, EPEAT
-------------------	------------------------------