


Key **Features**

- · Advanced Projected Capacitive (PCAP) touch technology
- Write Naturally and Accurately with Smart Active Pen
- · Azure certified IoT sensor hub for workplace management
- High Quality Video Conferencing Solution
- Single cable content sharing through USB Type C



Product **Description**

The ViewBoard® IFP70, our flagship interactive display, is tailored for visual collaboration in a digital workplace. Adopting advanced Projected Capacitive (PCAP) touch technology, it has a frameless, flat touchscreen to deliver precise responsiveness and the most accurate touch experience. Together with the smart pen, it enables you to write naturally and accurately like a real pen on a 4K Ultra HD resolution screen, streamlining visual collaboration. The ViewBoard® IFP70 series has quick, easy connectivity for content sharing via USB-C cable or wireless ViewBoard® Cast. Furthermore, it has a high quality video conferencing solution for the remote workforce with certified FHD camera, 6 mic array and 2.1 speaker configuration. In addition, the ViewBoard® IFP70 series gives you extra security to keep your information safe, private and compliant. It has built-in, AWS-powered myViewBoard™ whiteboarding software and an optional Intel® vPro™ slot-in PC. The ViewBoard® IFP70 series is also equipped with IoT sensors, which meet Windows Collaboration Display standards. It can work with Microsoft Azure Digital Twins to monitor and optimise your smart meeting rooms and collaboration spaces.



18. Audio Out

19. LAN

Visit Us - www.viewsonic.com

11. Touch X 2

12. Display Port

		datasileet_iiFF0070	
DISPLAY		BUNDLE SOFTWARE	
Panel Size:	86"	Basic Annotation Software:	myViewBoard for android
Type/Tech:	TFT LCD Module with DLED Backlight.	Pro Annotation Software:	myViewBoard for windows (Embedded in Windows Slot-in PC)
Display Area (mm):	1895.04 (H) x 1065.96 (V) (85.6"diagonal)	Wireless Presentation with Touch Feedback: Viewboard Cast:	Yes
Aspect Ratio:	16:9	Zoom:	Yes
Native Resolution:	UHD 3840x2160(Pixels)	ViewSonic Launcher:	Embedded
Colours:	1.07B colours (10bit)	SPECIAL FEATURES	
Brightness:	350 nits (typ.)	All-in-one USB port (combine	
Contrast Ratio:	1200:1 Typ.	Windows/Android USB port; no need to distinguish them	Yes
Response Time:	8ms	anymore):	
Viewing Angles:	H = 178, V = 178 typ.	Simple LAN sharing between IFP and slot-in device:	Yes
Backlight Life:	30,000 Hours (Min)	POWER	
Surface Treatment:	Anti-Glare/anti finger print	Voltage:	100-240VAC +/- 10% Wide Range
Bezel:	Slim		On:176.6W(Typ.)
Orientation:	Landscape	Consumption:	Off: <0.5W
PLATFORM	Lanuscape	ERGONOMICS	
	Dual core A73+Dual core A53	Wall Mount (VESA®):	800 x 600
Processor:		OPERATING CONDITIONS	
RAM:	4GB DDR4	Temperature (° C):	0°C to 40°C
Storage:	32GB	Humidity:	10% ~ 90% RH non-condensing
TOUCH		DIMENSIONS (W X H X D)	
Type/ Tech: Touch Resolution:	PCAP 32767 x 32767	Physical (inch / mm):	1962X1146X84(mm) 77.24x45.11x3.3(inch)
Touch Point:	20 points touch, 10 points writing	Packaging (inch / mm):	2123X1345X280(mm) 83.8X52.9X11(inch)
NPUT		WEIGHT	,
HDMI:	2.0 x1 (3840x2160 @60Hz)	Net (lb / kg):	160.93/73Kg
DisplayPort:	X1 1.4	Gross (lb / kg):	209.43/95Kg
RS232:	x1	REGULATIONS	200.40/00Ng
OPS:	x1 PC Slot (proprietary)	REGULATIONS:	FCC, cTUVus, CB, CE, RCM,
OUTPUT		ENERGY STAR VERSION	TOO, CTOVUS, OD, OL, NOW,
HDMI:	X1(4K2K@60Hz)	Energy Star version:	Under proceed apply to ES8.0
Audio:	x1 (Earphone out)	EEI RATING	onder product apply to 200.0
SPDIF:	1(optical)	EEI rating:	A+
LAN		PACKAGE CONTENTS	7.
RJ45:	x1	TACINGE CONTENTS	1. Power cable (3 metres) x 4 2. Remote control 3. AAA battery X2 4. USB cable Type C (1.5 metres pass logo) 5. active Touch pen x 2 6. Pen Charger X1 7. Quick Start Guide 8. RS232 adapter 9. Clamp x 7 10. Camera 11. Screw x 6 (4 for wall mount ,2 fisensor hub)
USB			
Type A:	USB 3.0 x3	PACKAGE CONTENTS:	
Type B:	USB 3.0 x2, for touch		
•	x1 USB3.0, DP1.4 Alternate mode,		
Type C:	Ethernet, PD 60W		
SPEAKERS			
SPEAKERS:	10W x 2 + 15W x 1 subwoofer		
CAMERA PLATE ON TOP FOR	SCREW-IN WEBCAM		12. HDMI cable (3 metres) 13. Sensor hub
INSTALLATION			14 .Touch USB cable (3 metres) 15. Micro USB cable for camera (2
Camera plate on top for screw-in webcam installation:	Yes	COMPATIBLE SLOT-IN PC	metres)
COMPATIBILITY		COMPATIBLE SLOT-IN PC	VPC14-WP series
CVBS:	480i	Commodible Clay : DO	VPC10-WP series
HDMI:	3840x2160	Compatible Slot-in PC:	VPC15-WP series VPC16-WP series
EMBEDDED OS			VPC17-WP series
Embedded OS:	Android 8		
USB SUPPORTED FILE FORMA	AT		
USB SUPPORTED FILE FORMAT:	Picture - BMP, JEPG, PNG Video - Codec: MPEG1, MPEG2, MPEG2-PS, MPEG4, MKV Container: MPG, MP4, MOV, VOB, DAT, MKV		
	Audio - Codec: AAC, HEAAC, MPEG1, MPEG2 Container: AAC, M4A, MP3		