

## E-Vision Laser 10K (Preliminary)

9,500 ANSI / 10,500 ISO ANSI Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part No:118-060

### E-VISION LASER 10K DIGITAL PROJECTOR



THE VISIONARIES CHOICE

**Colour System:**

Laser Phosphor + 4-segment (RGBW) colour wheel for high brightness

**DMD Specification:**

1920 x 1200 pixels native, +/- 12° tilt angle  
Fast transit pixels for smooth greyscale and improved contrast.

**Display Type:**

1 x 0.67" DarkChip™ DMD™

**Aspect Ratio:**

16x10

**Fill Factor**

87%

## Key Features

### Video & Graphics Processing

- HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources
- Dual Pipe Processing: Two sources in parallel for Left and Right eyes.
- Synchronisation of active glasses.
- 3GSDI with loop-through.
- 24p and 1080p native display.
- DICOM simulation mode.

### Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens.

### Edge Blending

- For independent edge and blend width adjustment.

### Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

### HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.

### Colour Processing

- Powerful seven point colour correction for accurate colour matching.

## Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

## Projector Automation

- Real-time clock provides daily on/off automation.

## Projector Maintenance Features

- Sealed optics.
- Long life 20,000 hour illumination.

## Source Compatibility:

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

HDMI including Deep Color™ processing.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.

Component Video (SD and HD) via RGBHV.

## Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DVI-D 1.0	DVI	1	3D Sync Out	BNC	1
DisplayPort 1.1a	DisplayPort	1	3D Sync In	BNC	1
HDMI 1.4b	HDMI	2	LAN	RJ45	1
3G-SDI in	BNC	1	RS232	9-pin D-Sub	1
3G-SDI out	BNC	1	Wired Remote	3.5mm Stereo Jack 1	
VGA / Analog RGB	15-pin D-Sub	1	12V Trigger	3.5mm Stereo Jack 2	
VGA Monitor out	15-pin D-Sub	1			
Component Video	5 x BNC	1			
HDBaseT (see LAN)	LAN RJ45	1			
			<b>NOTE: The LAN port is shared with HDBase-T.</b>		

## 3D Formats Supported

Frame Packing  
Dual Pipe  
Frame Sequential  
Side By Side (half)  
Top and Bottom

## HDTV Formats Supported

1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)

## Computer Compatibility

Up to 1920 x 1200

## Bandwidth

165 MHz on analog RGB  
165 Megapixels per second on HDMI

## Remote Control

Addressable IR remote control, wireless and wired.  
On-Board keypad.

## Automation Control

Crestron RoomView® Connected  
PJLink Class 1  
LAN  
RS-232  
AMX (Device Discovery)  
Served web page

## Colour Temperature

3200 to 9300K

## Lamp Type

Laser Light Source

## Typical Lamp Life

20,000 hours

## Lenses

Lens	Part No.	Focus Range	Lens Shift
------	----------	-------------	------------

0.38 :1 fixed	117-341	0.68m - 2.44m	none
0.76 :1 fixed	112-499	0.81m - 5.08m	none
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.72 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame

## Lens Mount

Motorised and programmable shift, zoom and focus.

Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).

## Mechanical Mounting

Front/Rear Table  
Front/Rear Ceiling  
Adjustable Front/Rear Feet

## Orientation

**Table Top or Inverted:** Yes  
**Pointing Up:** Yes  
**Pointing Down:** Yes  
**Roll (Portrait):** Yes

## Power Requirements

100-240VAC 50/60Hz single phase

## Power Consumption

Typical 1215W @ 240VAC in Normal mode  
Typical 960W @ 240VAC in ECO mode  
Typical 1270W @ 110VAC in Normal mode  
Typical 1000W @ 110VAC in ECO modeW

## Thermal Dissipation

Typical 4146 BTU/Hour @ 240VAC in Normal mode  
Typical 3276 BTU/Hour @ 240VAC in ECO mode  
Typical 4334 BTU/Hour @ 110VAC in Normal mode  
Typical 3412 BTU/Hour @ 110VAC in ECO mode  
BTU/Hour

## Fan Noise

Normal mode: 42 dBA Typical  
Eco mode: 39 dBA Typical

## Operating/Storage Temperature

Operating: 0 to 40C (32 to 104F)  
Operating: 40 to 45C (104 to 113F) w/ reduced light output  
Storage: -20 to 60C (-4 to 140F)

## Operating Humidity

10 to 90% relative, non-condensing

## Weight (Chassis Only)

28 kg  
62 lb

## Dimensions

L: 58.0 cm W: 50.0 cm H: 21.6 cm  
L: 22.8 in W: 19.7 in H: 8.5 in

## Safety & EMC Regulations

CB, CE, FCC Class 1, UL/cUL, CCC, RoHS 2  
IEC EN 60825-1 Class 3R Laser Product,  
IEC EN 62471-5 Risk Group 2

## Accessories

### Accessory

Infrared Remote (replacement)

### Part No.

117-780

*\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

## Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[User Guides German](#)

[User Guides French](#)

[Important Information](#)



Certificate Number 13629  
ISO 9001

---

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.  
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

---

**DIGITAL PROJECTION, LTD** GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX  
T: +44.161.947.3300 | F: +44.161.684.7674 | [www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144  
T: 770.420.1350 | F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** TOWER C, RM C1202, CAI FU JIA YUAN, NO. 19 XIAO YING STREET, CHAOYANG DISTRICT BEIJING,  
PR CHINA 100101  
T: +86.10.58239771 | F: +86 10 58239770

**DIGITAL PROJECTION, ASIA** 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204  
T: +65.6284.1138 | F: +65.6284.1238