

Packing 12,000 lm Brightness into a Compact Body, the PT-RZ120 Dual-Drive SOLID SHINE Laser Projector Lets You Do More



PT-RZ120/L	
Resolution	WUXGA
Brightness	12,000 lm
Contrast	10,000:1

Note: PT-RZ120L offers the same performance as PT-RZ120, but comes without a lens.

High-Quality Pictures and Long-Lasting Reliability

- Combines 1-Chip DLP™ imaging with proprietary SOLID SHINE Laser technology for accurate and immersive pictures at 12,000 lm
- Dynamic Light Control for 10,000:1*1 contrast
- Accurate white balance and color reproduction in any projection mode
- High picture quality maintained for very long periods
- Detail Clarity Processor 3 clarifies and enhances the finest details
- System Daylight View 3 optimization for sharp and vivid images in bright environments

Consistently Stable and Reliable Performance

- Dust-resistant projector structure with airtight optical block
- Dual-drive laser optical engine with dual phosphor wheels assures reliable 24/7 operation with light-source failover protection
- Up to 20,000 hours of continuous maintenance-free operation*2
- Efficient cooling system for stable operation in ambient temperatures of up to 45 °C (113 °F)*3
- High-speed backup input switching prevents screen blanking during projection

Versatile System Adaptability and Flexible Installation

- Shares optional lenses with Panasonic 1-Chip DLP™ projector family
- Compact body and free 360-degree installation (vertical and horizontal)
- DIGITAL LINK/HDMI® support transmission of uncompressed 4K signal
- Built-in Geometric Adjustment for projection onto specially shaped screens
- Supports Geometry Manager Pro and optional Upgrade Kit (ET-UK20)
- Auto Screen Adjustment Upgrade Kit (ET-CUK10)
- Direct Power Off function allows projector shutdown from mains

*1 With Dynamic Contrast Mode set to 3. *2 At 20,000 hours, projector brightness will have decreased to approximately half of its original level (Dynamic Contrast Mode: 3, Image Mode: Dynamic). Panasonic recommends cleaning or checkup at point of purchase after every 20,000-hour period (approximately). Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. *3 Light output may be reduced to protect the projector depending on environmental conditions.

Specifications (Tentative)

Model	PT-RZ120/RZ120L	
DLP™ chip	Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
	Display method	DLP™ chip x 1, DLP™ projection system
	Pixels	2,304,000 (1920 x 1200) pixels
Lens	PT-RZ120: Powered zoom (throw ratio 1.7–2.4:1), powered focus F 1.7–1.9, f 25.6–35.7 mm PT-RZ120L: Optional powered zoom/focus lenses	
Light source	Laser diodes laser Class 1 (Class 3R for US models)	
Screen size (diagonal)	1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE030, 16:10 aspect ratio	
Brightness*1	12,000 lm	
Center-to-corner uniformity*1	90 %	
Contrast*1	10,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)	
Resolution	1920 x 1200 pixels	
Optical axis shift*2	Vertical (from center of screen)	+50 %, -16 % (+40%, -16% with ET-DLE060) (powered)
	Horizontal (from center of screen)	+30 %, -10 % (+19%, -10% with ET-DLE060 / +28 %, -10 % with ET-DLE085) (powered)
Keystone correction range	Vertical: ±40° (±16° with ET-DLE060, ±22° with ET-DLE085/DLE055, +5° with ET-DLE030), Horizontal: ±15° (±10° with ET-DLE060) (cannot be operated with ET-DLE030)	
Keystone correction range with optional Upgrade Kit ET-UK20	Vertical: ±45° (±16° with ET-DLE060, ±40° with ET-DLE150/DLE250 / supplied lens, ±22° with ET-DLE085/DLE055), Horizontal: ±40° (±10° with ET-DLE060, ±15° with ET-DLE085/DLE055), Up to a total of ±55° during simultaneous horizontal and vertical correction.	
Installation	Ceiling/floor, front/rear, free 360-degree installation	
Terminals	SDI IN	BNC x 1: 3G/HD/SD-SDI input
	HDMI IN	HDMI 19-pin x 1 (Deep Color, compatible with HDCP)
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/Y/PbPr/YCbCr/YC/VIDEO
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/Y/PbPr/YCbCr
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX, compatible with PLink™ (Class 2)
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection, 100Base-TX, compatible with PLink™ (Class 2), HDCP, Deep Color
	Power supply	AC 100–240 V, 50/60 Hz
Power consumption	TBD	
Operation noise*1	TBD	
Cabinet materials	Molded plastic	
Dimensions (W x H x D)	PT-RZ120: 498 x 200*3 x 581 mm (19 19/32" x 7 7/8"*3 x 22 7/8") (with supplied lens) PT-RZ120L: 498 x 200*3 x 538 mm (19 19/32" x 7 7/8"*3 x 21 3/16") (without lens)	
Weight*4	TBD	
Operating environment	Operating temperature: 0–45 °C (32–113 °F)*5, operating humidity: 10–80 % (no condensation)	
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Geometry Manager Pro	

Note: PT-RZ120L offers the same performance as PT-RZ120, but comes without a lens.

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Optical axis shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE030. *3 With legs at shortest position. *4 Average value. May differ depending on the actual unit. *5 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector.

Optional Accessories

■ Fixed-Focus Lens ET-DLE030

■ **Zoom Lens**
ET-DLE085 / ET-DLE150 /
ET-DLE250 / ET-DLE350 /
ET-DLE450 / ET-DLE055 /
ET-DLE060

■ **Ceiling Mount Bracket**
ET-PKD130H (6-axis, for high ceiling)
ET-PKD120H (for high ceiling)
ET-PKD120S (for low ceiling)

■ **Projector Mount Bracket**
ET-PKD130B

■ **Geometry Manager Pro Software
Upgrade Kit**
ET-UK20

■ **Auto Screen Adjustment Upgrade Kit**
ET-CUK10

■ **Early Warning Software**
ET-SWA100 Series

■ **DIGITAL LINK Switcher**
ET-YFB200G

■ **Digital Interface Box**
ET-YFB100G

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. PLink™ is a registered trademark or pending trademark in Japan, the United States, and other countries and regions. All other trademarks are the property of their respective trademark owners. © 2018 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojector
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of February 2018.

PT-RZ120PRE1 Printed in Japan.