



Large-scale screens no longer fear the “tensioning test”.

In addition to its trademark 150 mm diameter aluminium roller, and the case which is open underneath, the Alumax screen can count on another formidable feature to guarantee the perfect planarity of large-scale canvases: the CTS (Constant Tension System), which ensures the constant self-tensioning of the screen by means of two counterweights hooked onto hinges placed at the ends of the screen’s base, devised for tensioning rigid cables threaded through lateral eyelets. This also prevents the formation of creases during rolling, since the eyelets are positioned outside the projection surface (see page 8).

The ideal technical solution for excellent projection even in the largest spaces.

Create your own screen with the PSS:

- > **personalized dimensions:** width and height
- > **roller type:** standard motorized
- > **case:** available only with case
- > **case color:** available in white or black
- > **projection surfaces:** ReferenceWhite, VisionWhite, VisionAcoustik and Vision MacroAcoustik only with black borders
- > **height of top:** from 10 to 20 cm
- > **projection surface drop:** front or rear
- > **side of command/motor:** right or left

Standard accessories:



- > kit with wall -or ceiling- quick mount brackets
- > unipolar selector switch

Optional accessories:

- > receiver and RF remote control for motorized screen (3 modalities: basic, automatic and compatible with domotic systems)
- > receiver and infrared remote control
- > bracket extensions for screens up to 60 cm



| Format | Overall Width | Overall Height | Surface Width | Surface Height | Net Surface Width | Net Surface Height | Standard Top | Maximum Total Top | Diagonal Inches | Shipment Sizes | Net Weight | Gross Weight |
|--------|---------------|----------------|---------------|----------------|-------------------|--------------------|--------------|-------------------|-----------------|----------------|------------|--------------|
| | A | E | F | G | H | I | P | cm | O | cm | kg | kg |
| 4:3 | 512 | 385 | 474 | 363 | 464 | 348 | 10 | 20 | 228 | 530x29x32 | 82 | 107 |
| | 612 | 460 | 574 | 438 | 564 | 423 | 10 | 20 | 278 | 630x29x32 | 100 | 125 |
| 16:9 | 512 | 298 | 474 | 276 | 464 | 261 | 10 | 20 | 210 | 530x29x32 | 80 | 105 |
| | 612 | 354 | 574 | 332 | 564 | 317 | 10 | 20 | 255 | 630x29x32 | 98 | 123 |
| | 712 | 410 | 674 | 388 | 664 | 373 | 10 | 20 | 300 | 730x29x32 | 120 | 145 |
| 16:10 | 512 | 327 | 474 | 305 | 464 | 290 | 10 | 20 | 215 | 530x29x32 | 80 | 105 |
| | 612 | 390 | 574 | 368 | 564 | 353 | 10 | 20 | 262 | 630x29x32 | 98 | 123 |
| | 712 | 452 | 674 | 430 | 664 | 415 | 10 | 20 | 308 | 730x29x32 | 120 | 145 |
| 21:9 | 512 | 235 | 474 | 212 | 464 | 197 | 10 | 20 | 199 | 530x29x32 | 80 | 105 |
| | 612 | 277 | 574 | 255 | 564 | 240 | 10 | 20 | 241 | 630x29x32 | 98 | 123 |
| | 712 | 320 | 674 | 298 | 664 | 283 | 10 | 20 | 284 | 730x29x32 | 120 | 145 |



Standard formats



4:3

PSS formats



21:9



16:9



16:10



5:4



1:1

Surfaces Fireproof Certification

