



PROJECTOR

**PX701HD**

## Key Features

- 3,500 ANSI Lumens with native Full HD 1080p
- Energy-efficient SmartEco+ Mode for lamp life up to 20,000hrs
- Vertical Lens Shift
- Colour Profile Preference with vColorTuner
- SuperColor™ technology




## Product Description

The ViewSonic PX701HD is a high brightness 3,500 ANSI lumens projector featuring a Full HD 1080p resolution that offers impressive visual performance in a brightly lit living room or meeting room. The projector adopts the latest lamp design to extend lamp life of up to 20,000 hours under SuperEco+ mode, effectively reducing lamp replacement and maintenance costs. A digital lens shift allows users to make adjustments by remote control, it's also compatible with the vColorTuner function for color profile exchange and adjustments. The dual HDMI inputs and USB power supply allow users to connect to a multitude of multimedia devices for gaming, movies, or a wireless dongle for wireless presentation.



1. Keypad
2. LED indicator
3. Power Key
4. Zoom/Focus
5. Front IR
6. Projection Lens
7. Audio in/out



8. Dual HDMI
9. USB Type A
10. Computer in
11. Monitor out
12. RS232
13. Kensington® Lock Slot

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**SPECIFICATION**

Native Resolution:	1920x1080
DMD Type:	DC3
Brightness:	3500 ANSI Lumens
Contrast Ratio with SuperEco Mode:	12000:1
Display Color:	1.07 Billion Colors
Light Source Type:	Lamp
Light Source Life (Normal):	5000
Light Source Life (SuperEco):	20000
Lamp Watt:	203W
Lens:	F=2.0~2.05,f=15.843mm~17.445mm
Projection Offset:	110%+/-6%
Throw Ratio:	1.5-1.65
Image Size:	30" - 300"
Throw Distance:	1m~10.96m (100"@3.32m)
Keystone:	+/- 40° (V)
Lens Shift V. Range:	Yes (+/- 5%)
Optical Zoom:	1.1x
Digital Zoom:	0.8x ~ 2.0x
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

**INPUT**

Computer in (share with component):	1
Audio-in (3.5mm):	1
HDMI:	2 (HDMI 1.4/ HDCP 1.4)

**OUTPUT**

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	10W
USB Type A (Power):	1 (5V/1.5A)

**CONTROL**

RS232 (DB 9-pin male):	1
------------------------	---

**OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 300W Standby: <0.5W
Operating Temperature:	0~35°C
Net Weight:	2.59kg
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm

OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
---------------	--

**STANDARD ACCESSORY**

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1

**OPTIONAL ACCESSORY**

Lamp/Light Source:	RLC-119
--------------------	---------