

ViewSonic® PROJECTOR PX706HD

Key Features

- Short throw projection
- 1.2X optical zoom
- USB Type-C input
- 3X fast input
- Gaming Mode



Product Description

The ViewSonic PX706HD is projector design for big screen gaming at home with a brightness of 3,000 ANSI Lumens, 1080p resolution, short throw lens and 1.2x adjustable zoom for flexible installation and the versatility to play games in any room in your house. The projector comes equipped with 3X Fast Input for more responsive gaming control via low input lag along with specialized game modes for clear image detail in dark scenes. Whether playing racing games, shooting games, or any other type of game, PX706HD optimizes screen performance and offers big screen visuals to take the excitement to the next level and makes multiplayer gaming more enjoyable. PX706HD has been designed with a Powerful audio provided by the projector's built-in 5W cube speakers along with SonicExpert and SonicMode enhancement deliver an immersive multisensory gaming experience.

Visit Us ■ www.viewsonic.com

SPECIFICATION

Native Resolution:	1920x1080
DC Type:	DC3
Brightness:	3000
Contrast Ratio with SuperEco Mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light Source Life (Nor/SuperEco):	4000/15000
Lamp Watt:	240W
Lens:	F=2.6-2.78f= 10.2~12.24
Projection Offset:	105%+/-5%
Throw Ratio:	0.69-0.83
Image Size:	60"~120"
Throw Distance:	0.9m-2.2m (100"@1.5m)
Keystone:	+/- 20° (Vertical)
Optical Zoom:	1.2x
Audible Noise (Eco):	27dB
Response Time:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Composite:	1
Audio-in (3.5mm):	1
HDMI (HDCP):	2 (HDMI 1.4/ HDCP 1.4)
USB Type C:	1 (5V/ 2A)

OUTPUT

Audio out (3.5mm):	1
Speaker:	5W Cube

CONTROL

RS232:	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 310WStandby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	2.7kg
Dimensions (WxDxH) with Adjustment Foot:	293x115x220 mm

Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
-----------	---

STANDARD ACCESSORY

Power Cord:	1
Remote Control:	1
QSG:	1
Lens Cover:	1
USB Type C:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-118
--------------------	---------