



PROJECTOR PS600X

Key Features

- Short throw ratio
- 15,000 hours lamp life
- HV keystone and 4 corner adjustment
- Dual HDMI inputs
- Built in USB type A for charging



Product Description

The PS600X is a high brightness XGA short throw projector for education. With the ability to project 100" images from a distance of 124cm from the projection surface, PS600X is flexible enough to fit any classroom design while keeping the presenter clear of the projection beam. A brightness of 3700 ANSI Lumens allows the projector to project clear, detailed images with the lights kept on so students can more easily take notes and maintain focus. The energy-saving SuperEco mode reduces power consumption and extends lamp life to a lengthy 15,000 hours. PS600X is compatible with PJ-vTouch-10S, the optional interactive module that turns class into an engaging interactive teaching environment. In addition, users can easily control and manage PS600X remotely via the LAN network solution for maximum efficiency.



Visit Us ■ www.viewsonic.com

SPECIFICATION

Native Resolution:	1024x768
DC type:	DC3
Brightness:	3700 ANSI Lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	190W
Lens:	F=2.6, f=6.9mm
Projection Offset:	130%+/-5%
Throw Ratio:	0.61
Image size:	60" - 300"
Throw Distance:	0.74m-3.72m (100" @ 1.06m)
Keystone:	HV
Optical Zoom:	Fixed
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (D-SUB 15 pin):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI/HDCP:	2 (HDMI 1.4/ HDCP 1.4)

OUTPUT

Monitor out (D-SUB 15 pin):	1
Audio out (3.5mm):	1
Speaker:	10W
USB type A (Power):	1 (5V/1A)

CONTROL

RS232:	1
RJ45:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.6kg
Dimensions (WxDxH) w/adjustment foot:	292x236x115mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1 (w/Laser pointer)
QSG:	1
Lens Cover:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-108
--------------------	---------