

# EB-1485Fi



Agile working through content sharing and flexible connectivity with this Full HD laser display solution.

Transform your workplace with this large, scalable display that enriches collaboration and engagement, and promotes greater knowledge sharing with colleagues, clients or delegates using the latest and most versatile connectivity options. The EB-1485Fi has been designed to be easy to use, enriching collaborative and agile working environments.

### Flexible display options and sizes

Deliver impactful sessions with a multi-touch display of up to 100 inches (16:9 standalone), 120 inches (16:6 standalone), or 155 inches using Epson's DuoLink feature, which combines two interactive display using built-in Edge Blending.

### Promotes collaboration and connectivity

The intuitive and easy-to-use UI, new touch home screen and new interactive OSD menu make it simple to set up and navigate across functions. Featuring multi-touch pen and finger capabilities, wireless BYOD connectivity and screen mirroring (Miracast). It also has secure user collaboration tools and an array of powerful connectivity options, both wireless and wired, including HDBaseT and HDMI out. The Epson iProjection App is available to download for free, providing seamless wireless connectivity and collaboration control from multiple devices and platforms. It's compatible with Windows, Office 365 suite and iOS, allowing the use of Office applications via PCs and tablets.

### Sliding split screen

Combine up to four sources, such as video conference systems from multiple video sources and presentations, to optimise meeting interactions.

### Fit and forget technology

Once installed, use for up to 20,000 hours without any maintenance, with the additional peace of mind of a five-year warranty. Helping to reduce running costs, and meaning you can 'fit and forget' and continue with the job in hand.

## DATASHEET / BROCHURE



## KEY FEATURES

- **Flexible display options and sizes**  
Cater for user needs in any working environment
- **All-in-one interactive meeting display**  
Combines multiple resources in one interactive collaboration device
- **Increase productivity & agile working**  
Share and display content from a range of devices simultaneously
- **Sliding split screen**  
Up to four displays in one image - project images from different sources
- **Easy installation**  
Quick set-up with auto-adjusting calibration function



**EPSON**  
**WORLD LEADER**  
**IN PROJECTORS**

Source: Futuresource Consulting Ltd.

**EPSON**<sup>®</sup>  
EXCEED YOUR VISION

## PRODUCT SPECIFICATIONS

### TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	0,62 inch with C2 Fine

### IMAGE

Colour Light Output	5.000 lumen- 3.500 lumen (economy)
White Light Output	5.000 lumen - 3.500 lumen (economy)
Resolution	Full HD 1080p, 1920 x 1080, 16:9
Aspect Ratio	16:9
Contrast Ratio	Over 2.500.000 : 1
Light source	Laser
Lamp	20.000 h durability, 30.000 h durability (economy mode)
Laser Light source	30.000 Hours Durability Eco
Keystone Correction	Manual vertical: $\pm 3^\circ$ , Manual horizontal $\pm 3^\circ$
Colour Processing	10 Bits
2D Vertical Refresh Rate	192 Hz - 240 Hz
Colour Reproduction	upto 1.07 billion colours

### OPTICAL

Projection Ratio	0,27 - 0,37:1
Zoom	Digital, Factor: 1 - 1,35
Lens	Optical
Image Size	65 inches - 100 inches
Projection Distance Wide	0,4 m ( 65 inch screen
Projection Distance Tele	0,6 m ( 100 inch screen
Projection Distance Wide/Tele	0,78 m ( 120 inch screen
Projection Lens F Number	1,5
Focal Distance	3,9 mm
Focus	Manual
Offset	9 : 1

### CONNECTIVITY

Interfaces	USB 2.0 Type A (2x), Powered USB, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac (WiFi 5), Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Component in, Miracast, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input, Finger-touch interface, Multi-Touch interface, USB 2.0 Type B (2x), Sync. in, Sync. out, HDMI out, HDBaseT
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink

### ADVANCED FEATURES

Security	Kensington lock, Control panel lock, Password lock, Padlock, Wireless LAN security, Password protection
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM SIM
Features	Arc Correction, Auto calibration, Auto Power On, Built-in speaker, CEC compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera Compatible, Driverless installation, Dual Pen Support, Easy OSD pre-setting, Email notification, Finger-touch support, Screen Fit, Freeze image, Image Shift, Instant on/off, Interactive, Interactive OSD menu, Mail notification function, Microphone input, Network administration, OSD copy function, PC Interactive, PC free annotation, iProjection App for Chromebook, Quick Corner, Schedule Function, Screen Mirroring, Screen share, Set-up wizard, Sliding split-screen feature, Split-Screen-Function, Super resolution, Web Control, Web Remote, Whiteboard sharing function, Wireless LAN capable, iProjection App, iProjection set-up by QR code
Interactivity	Yes - pen and finger-touch
Video Colour Modes	Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM SIM
Projector control	via: AMX, Crestron (Network), Extron, Crestron (RS-232c only), Crestron Integrated Partner, Crestron RoomView, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol

## EB-1485Fi

### WHAT'S IN THE BOX

- CD Manual
- Interactive pens
- Power cable
- Remote control incl. batteries
- Replacement pen tips
- Pen Holder/Stand
- Cable cover
- 2 x Pen tip(Teflon)
- Lens cap
- 4 x Pen tip(Felt)
- HDBaseT Control Pad
- Wall mounting bracket
- Finger touch unit



**EPSON**  
**WORLD LEADER**  
**IN PROJECTORS**  
 Source: Futuresource Consulting Ltd.

**EPSON**<sup>®</sup>  
 EXCEED YOUR VISION

---

## PRODUCT SPECIFICATIONS

---

### GENERAL

Energy Use	366 W, 262 W (economy), 0,5 W (standby)
Heat Dissipation	1.244 BTU/hour (max)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Product dimensions	458 x 375 x 210 mm (Width x Depth x Height)
Product weight	9,3 kg
Noise Level	Normal: 36 dB (A) - Economy: 27 dB (A)
Temperature	Storage -10° C - 60° C
Included Software	Easy Interactive Tools, Epson Projector Management Software
Options	Document camera, External Speaker, Pen tip(Felt), Pen tip(Teflon), Wireless LAN unit
Compatible Operating Systems	Linux, Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Ubuntu 14.10, Ubuntu 15.04
Loudspeaker	16 W, Stereo: Stereo
Room Type / Application	Boardroom, Collaboration space / Classroom
Positioning	Table Mounted, Wall Mounted
Colour	White

---

### OTHER

Warranty	60 months Carry in or 12.000 h Optional warranty extension available
----------	---

---

---

## EB-1485Fi

---

### WHAT'S IN THE BOX

---

- CD Manual
- Interactive pens
- Power cable
- Remote control incl. batteries
- Replacement pen tips
- Pen Holder/Stand
- Cable cover
- 2 x Pen tip(Teflon)
- Lens cap
- 4 x Pen tip(Felt)
- HDBaseT Control Pad
- Wall mounting bracket
- Finger touch unit

---

## OPTIONAL ACCESSORIES

---

---

EB-1485Fi

---

- ELPFT01 - Finger Touch Unit  
V12H007A24
- Active Speakers (2 x 15W) - ELPSP02  
V12H467040
- Replacement Soft Pen Tip - ELPPS04 (12pcs)  
V12H776010
- Replacement Hard Pen Tip - ELPPS03 (6pcs)  
V12H775010
- Interactive Pen - ELPPN05B - Blue - EB-6xxWi/Ui / 14xxUi  
V12H774010
- Interactive Pen - ELPPN05A - Orange - EB-6xxWi/Ui / 14xxUi  
V12H773010
- Dual Function Wireless Adapter (5Ghz Wireless & Miracast) -ELPAP11  
V12H005A01
- ELPMB63 - Finger Touch Wall Bracket for ELPFT01  
V12HA05A09
- Air Filter - ELPAF56 - L600/EB-14XX Series  
V13H134A56

## LOGISTICS INFORMATION

SKU	V11H919040
EAN code	8715946674070
Country of Origin	China



TEKSEL d.o.o.  
Tržaška cesta 132  
1000 Ljubljana  
Tel.: +386 1 620 77 25  
Faks: +386 1 620 77 26  
Splet: [www.teksel.si](http://www.teksel.si)  
E-pošta: [info@teksel.si](mailto:info@teksel.si)

Blagovne znamke ali registrirane blagovne znamke so last podjetja Seiko Epson Corporation ali njihovih lastnikov. Informacije o izdelkih se smejo spremeniti brez vnaprejšnjega opozorila.

**EPSON®**