# IFM55TH652/4



# 55" Interactive Flat Panel Displays - IFM series


VES

### **Key Features**



### Collaborate, Annotate with Oktopus

Collaborate: View lessons, respond, share annotations, and take notes using any tablet or laptop Anntate: Works over browser content & existing applications Poll: Pose questions and gain immediate participant feedback, displaying results instantly.



### HDR10 & 4K HDMI @60Hz

Displays supporting HDR10 allows HDR based content to be shown, giving a brighter and more dynamic picture. This is further enhanced due to the support of 4K 60Hz, allowing ultra sharp, smooth Video content to be presented.



### **Anti Glare Tempered Glass**

Prevents light reflection and provides smooth touch performance with anti glare technology. Robust design with toughened glass material to avoid any damage to the screen



### Simultaneous Smooth writing Multi - Touch

10 point touch support detects multiple touch points, enhancing the possibility of collaborative work. The screens also provide a precise and user friendly writing experience with its smooth surface.

## IFM55TH652/4



### PANEL

Screen Size Panel Technology Backlight Type Brightness (typical) Native Resolution Contrast Ratio (typical) Dynamic Constrast Ratio Panel Life Time (Min.) Response Time (typical) Active Area (H x V) Viewing Angle Color Value Screen Treatment Haze Level Refresh Rate Front Type Orientation Operation Hours Area of Usage

55" IPS Direct-Type LED 400 cd/m<sup>2</sup> 3840 x 2160 (16:9) - UHD 1300:1 40000:1 30000 Hr 6 ms 1210 x 681 mm 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 16.7 M (8-bit) 2H 3% 60 Hz Black Super Narrow Bezel Horizontal 16/7 Indoor

### MONITOR CONNECTIVITY

RGB Input RGB Output Video Input Video Output Audio Input Audio Output External Control External Sensor VGA(DE-15F) N/A 4xHDMI2.0, 2xUSB2.0, USB2.0(Internal) HDMI2.0 Line In L/R Headphone, Optic SPDIF RS232(DE-9F), Ethernet(RJ45), Service(RJ12) RJ12

# MECHANICAL

Product Dimensions (WxDxH) Package Dimensions (WxDxH) Product Weight Package Weight Vesa Mounting Bezel Width

1280 x 123 x 751 mm 1480 x 265 x 930 mm 29.45 kg 38.15 kg 400 x 200 mm B:34 | T:34 | L/R:34 mm

#### POWER

Power Supply

110 VAC - 240 VAC

### FEATURES

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock
Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance
Speaker	2 x 8 W

### CERTIFICATION

Safety	YES
EMC	YES
CE	YES

### MAINBOARD

Mainboard Model

17MB135VS

### TOUCH TECHNOLOGY

Type of Touch Technology Supported Point Sensitivity Connectivity Supported OS and Applications

Orientation Calibration Accuracy Reporting Rate Glass Type Frame Rate Communication Power Supply Mode Supply Voltage Average Current Response Time Touch Accuracy Object Sizes for Touch Touch Durability HID Compatibility 10 Points Any touch with finger, gloved hand or pointer HID, TUIO, Flash Windows<sup>®</sup>7, Windows<sup>®</sup>8, Windows<sup>®</sup>10, Vista, XP, Mac<sup>®</sup> OS, Linux, Android Landscape support No need %90 Up to 450 fps Anti Glared (AG), 4mm Tempered up to 450 fps USB 2.0 USB DC 5V +/- 5%

+/-2mm (over 90% area) 5mm Unlimited Yes USB

Infrared (IR) Technology

### ENVIRONMENTAL CONDITIONS

Operating Temperature Operating Humidity +40°C / 0°C 90%

### POWER CONSUMPTION

83 W ≼0.5W

### ACCESSORY

Standard

Typical

Deep Standby

QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable

