

# Thunder-KMT18 I

High-tech, multi-task powered 18" subwoofer with DSP and power output



## DESCRIPTION

The K-array Thunder-KMT18 I is a powered 18" subwoofers, with a programmable on-board DSP and multiple analog and digital inputs and outputs for creating a wide array of speaker configurations. The amplifier mounted on board is class D, delivering 2 x 1000 W at 8Ω.

The KMT18 I features an integrated touch screen, providing intuitive control over the main DSP functions: input/output levels, signal routing, offset delays for subwoofer and speakon output (up to 12 ms) and overall system delay (up to 330 ms).

All DSP functions, including EQ, can also be remote controlled via software over USB or RS485 (3-pin XLR).

The KMT series provides two balanced analog line level inputs and a two-channel AES/ EBU digital input. An integrated class D amplifier delivers 2 x 1000 W at 8Ω, with a max THD of 1% (EIAJ test @ 1kHz). The KMT18 I features multiple analog and digital outputs, including a Speakon output to connect a wide array of passive speakers including midhigh models (KK52, KK102) or additional passive subwoofers (KMT18P). To

optimize performance, the on-board DSP includes up to 40 programmable presets. The unique four-corner port configuration provides symmetrical back loading to the speakers, for extended bass response with very low distortion. The port configuration also provides incredible structural strength to the cabinet, despite its light weight. Pocket handles and an M20 thread mount position for attaching mid-high speakers makes the subwoofer convenient to use and ideal for medium throw applications in theaters, concert halls, and Audio/Video installations.

## COLORS & PREMIUM FINISHES AVAILABLE



Black



White



Custom

## SUGGESTED ACCESSORIES

K-DANTE

K-AMPCOVER

K-POLE1

K-WHEEL

K-USB

K-WHEELB

## FEATURES



Lightweight



On-Board Touch Screen



Compatible

## FREQUENT APPLICATIONS

THEATERS & CONCERT HALLS

NIGHTCLUBS

EVENT PRODUCTIONS

RETAIL

BROADCAST & STUDIOS

THEME PARKS

HOTELS

## TECHNICAL SPECIFICATIONS

ACOUSTICS		REMOTE CONTROL INPUT	
Power handling	800W <sup>(AES)</sup>	Connectors	1 male + 1 female XLR parallel / 1 USB B Jack serial converter
Max Power	1400 W	POWER INPUT	
Impedance	8 Ohm	Connectors	2 x PowerCon IN/OUT
Frequency range	30 Hz - 150 Hz ± 3dB (preset relating)	AMPLIFIERS	
SPL 1W/1mt	99 db	Type	1 modules class D - DSP controlled
Maximum SPL3	130dB (cont) - 136dB (peak)	Subwoofer power	1000 Watt <sup>1</sup> @ 8Ω
COVERAGE		Speaker power output	1000 Watt <sup>1</sup> @ 8Ω
Type	Omni	Protections	Dynamic limiter, over current, over temp, short circuits
CROSSOVER		AC POWER	
Type	DSP controlled	Nominal power requirements	100 - 240 Vac ± 10% 50-60 Hz
Frequency	150 Hz (preset dependent)	Operating range	85 - 265 Vac (auto-range)
TRANSDUCERS		CONSUMPTION	
Full range	1 x 18" Neodymium speakers with 3" voice coil	1/8 rated power (pink noise) @ 8Ω	300 W
POWER AUDIO INPUT		PHYSICAL	
Analog Connectors	2 male + 2 female 3-pin balanced XLR	Dimensions	46.5 x 46.5 x 59.6 cm (18.30" x 18.30" x 23.46") <sup>(2)</sup>
Digital Connectors	1 male + 1 female 3-pin XLR	Weight	27.6 Kg (60.84 lb)
AUDIO POWERED OUTPUT			
Connector	Female Speakon		
Wiring	Pin1+= CH1+ Pin1= CH1- Pin2+= N.C. Pin2= N.C.		
<p>1. Amplifier wattage rating is based on the maximum unclipped burst sine wave RMS voltage that the amplifier will produce into the nominal load impedance.</p> <p>2. ( W x H x D)</p>		<p>New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from w those presented in this catalogue.</p>	

