

# ViewSonic® PROJECTOR PG701WU

## Key Features

- SuperEco+ Mode
- Customized user modes
- 5V/1.5A USB power for wireless dongle
- Dual HDMI inputs
- SuperColor™ technology




## Product Description

The ViewSonic PG701WU is a high brightness WUXGA projector with 1920 x 1200 resolution and a 16:10 aspect ratio. The 3,500 ANSI lumens of brightness allows the PG701WU to project images in full depth and detail, even in brightly lit medium-sized spaces, such as meeting rooms or classrooms. Its new SuperEco+ mode extends the projector's lamp life of up to 20,000 hours, effectively reducing lamp replacement and maintenance costs. In addition, the dual HDMI ports allow you flexibly connect to your laptop, PC, and other high definition devices for presentation files or multimedia applications. Lastly, the USB Type A with power supply provides connectivity to a USB dongle for a wireless presentation.



1. Keypad
2. LED indicator
3. Power Key
4. Zoom/Focus
5. Front IR
6. Projection Lens
7. Audio in/out



8. Dual HDMI
9. USB Type A
10. Computer In
11. Monitor Out
12. RS232
13. Kensington® Lock Slot

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**SPECIFICATION**

Native Resolution:	1920x1200
DMD Type:	DC3
Brightness:	3500 ANSI Lumens
Contrast Ratio with SuperEco Mode:	12000:1
Display Color:	1.07 Billion Colors
Light Source Type:	Lamp
Light Source Life (Normal):	5000
Light Source Life (SuperEco):	20000
Lamp Watt:	203W
Lens:	F=2.0~2.05, f=15.843-17.445mm
Projection Offset:	100% +/-6%
Throw Ratio:	1.5-1.65
Image Size:	30" - 300"
Throw Distance:	0.97m~10.67m(100" @3.23m)
Keystone:	+/- 40° (V)
Optical Zoom:	1.1x
Digital Zoom:	0.8x ~ 2.0x
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

**INPUT**

Computer in (share with component):	1
Audio-in (3.5mm):	1
HDMI:	2 (HDMI 1.4/ HDCP 1.4)

**OUTPUT**

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W
USB Type A (Power):	1 (5V/1.5A)

**CONTROL**

RS232 (DB 9-pin male):	1
------------------------	---

**OTHERS**

Power Supply Voltage:	100-240V +/- 10%, 50/60Hz AC
Power Consumption:	Normal: 300W Standby: <0.5W
Operating Temperature:	0~35°C
Net Weight:	2.57kg
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

**STANDARD ACCESSORY**

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1

**OPTIONAL ACCESSORY**

Lamp/Light Source:	RLC-119
--------------------	---------