EB-PU2220B

DATASHEET / BROCHURE





The EB-PU2220B is the world's smallest and lightest 20,000lm projector¹.

The EB-PU2220B offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

Compact and lightweight

The EB-PU2220B is 70% smaller and 50% lighter than its predecessor, the EB-L20000U. The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

Flexibility

The EB-PU2220B's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes improved dustproofing as the hermetically sealed optical engine, and laser light source unit, prevent dust contamination to ensure enhanced durability.

KEY FEATURES

- Ultra-lightweight and compact The world's smallest and lightest 20,000lm projector¹
- Stunning image displays 20,000lm, 4K Enhancement technology, WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability Enhanced dustproof construction. IP5x certified
- Environmental benefits Lower power consumption, reduced packaging, reduced weight





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1,03 inch with C2 Fine	
IMAGE		
Color Light Output	20.000 Lumen- 14.000 Lumen (economy) In accordance with IDMS15.4	
White Light Output	20.000 Lumen - 14.000 Lumen (economy) In accordance with ISO 21118:2020	
Resolution		
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	Over 2.500.000 : 1	
Native Contrast	2.000 : 1	
Light source	Laser	
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco	
Colour Video Processing	10 Bits	
Colour Reproduction	Upto 1.07 billion colours	
·		
OPTICAL		
Throw Ratio	0,35 - 7,41:1	
Zoom	Motorized, Factor: 1 - 1,6	
Lens	varies by lens	
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens	
Lens position memory	10 positions	
Screen Size	60 inches - 1.000 inches, varies by lens	
Projection Distance Wide)varies by lens	
Projection Distance Tele)varies by lens	
Projection Lens F Number	varies by lens	
Projection Lens Focal Length	varies by lens	
Projection Lens Focus	Motorized	
Interchangeable Lens	Yes	
Standard Lens	Not included	
CONNECTIVITY		
Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100-	
	Base TX/ 10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, 3G-SDI Input, 3G-SDI	
	Output, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC)	
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Security	Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security,	
ocounty	Password protection	
Other features	4K enhancement, Auto Power On, Auto source search, Direct Power on/off, Edge Blending,	
	Lens position memory, Long light source life, OSD copy function, Power on button, Quick	
	Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web	
Video Color Modeo	Remote, iProjection App	
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709	
Projector control	via: AMX, Crestron, Extron	

EB-PU2220B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

GENERAL		
Power consumption	1.301 Watt, 899 Watt (economy), 0,4 Watt (standby), On mode power consumption as defined	
	in JBMS-84 1.143 Watt	
Heat Dissipation	4.423 BTU/hour (max)	
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz	
Product dimensions	586 x 492 x 218 mm (Width x Depth x Height)	
Product weight	24,4 kg	
Noise Level	Normal: 45 dB (A) - Economy: 37 dB (A)	
Supported Temperature	Storage -10° C - 60° C	
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager,	
	Epson Projector Management, Epson Projector Professional Tool	
Options	Ceiling mount, Wireless LAN unit	
Positioning	Ceiling Mounted, Desktop, Flying Frame	
Colour	Black	
OTHER		
Warranty	36 months Carry in	
	Optional warranty extension available	

EB-PU2220B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



OPTIONAL ACCESSORIES

- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Camera Unit ELPEC01 V12HA46010
- Ceiling Mount ELPMB68
- V12H006AE0
- Extension Pole ELPMB70 For ELPMB68 V12H006AG0
- Truss Adaptor ELPMB71 For ELPMB68 V12H006AH0
- Stacking Frame ELPMB59 L1000 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLL08 Long throw EB-PU Series V12H004L08
- Lens ELPLM10 Mid throw 3 EB-PU Series V12H004M0A
- Lens ELPLM11 Mid throw 4 EB-PU Series V12H004M0B
- Lens ELPLM15 Mid throw EB-PU Series V12H004M0F
- Lens ELPLU03S Short throw off axis 1 EB-PU Series V12H004UA3
- Lens ELPLU04 Short throw off axis 2 EB-PU Series V12H004U04
- Lens ELPLW06 Wide zoom 2 EB-PU Series V12H004W06
- Lens ELPLW08 Wide throw EB-PU2000 Series V12H004W08
- Lens ELPLX02S UST EB-PU2000 Series V12H004X0B
- Lens ELPLX02WS UST EB-PU2000 Series V12H004Y0B

LOGISTICS INFORMATION

ѕки	V11HA66840
EAN code	8715946703213
Country of Origin	China



TEKSEL d.o.o. Tržaška cesta 132 1000 Ljubljana Tel.: +386 1 620 77 25 Faks: +386 1 620 77 26 Splet: www.teksel.si E-pošta: info@teksel.si

Blagovne znamke ali registrirane blagovne znamke so last podjetja Seiko Epson Corporation ali njihovih lastnikov. Informacije o izdelkih se smejo spremeniti brez vnaprejšnjega opozorila. EB-PU2220B

in accordance with ISO 21118.

1. As of December 2021. Main unit without lens. 20,000lm