

# Exceptional projectors for installation, rental and staging



Model	EB-L530U	EB-L630SU EB-L635SU	EB-L630U* EB-L730U EB-L735U	EB-PU1006W	EB-PU1007W EB-PU1007B	EB-PU1008W EB-PU1008B	EB-PU2010W EB-PU2010B	EB-PU2113W EB-PU2213B	EB-PU2116W EB-PU2216B	EB-PU2120W EB-PU2220B	EB-L30002U EB-L30000U
Colour Light Output (lumens) normal / eco	5200 / 3640	6000 / 4200	6200 / 4340* 7000 / 4900	6000 / 4200	7000 / 4900	8500 / 5950	10000 / 7000	13000 / 9100	16000 / 11200	20000 / 14000	30000 / 20000
Resolution	WUXGA	WUXGA	WUXGA	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement
Noise (dB) normal / eco	31 / 23	38 / 27	38 / 27	30 / 28	33 / 29	35 / 30	37 / 30	34 / 29	38 / 34	45 / 37	49 / 41
Throw ratio in native aspect	1.35 - 2.20:1	0.8:1	1.35 - 2.20:1	1.44 - 2.32:1 <sup>1</sup>	1.44 - 2.32:1 <sup>1</sup>	1.44 - 2.32:1 <sup>1</sup>	1.57 - 2.56:1 <sup>2</sup>	1.57 - 2.56:1 <sup>2</sup>	1.57 - 2.56:1 <sup>2</sup>	1.57 - 2.56:1 <sup>2</sup>	1.74 - 2.35:1 <sup>3</sup>
Dimensions (W x D x H mm)	440 x 339 x 136	440 x 334 x 136	440 x 339 x 136	545 x 436 x 164	545 x 436 x 164	545 x 436 x 164	545 x 436 x 164	586 x 492 x 185	586 x 492 x 185	586 x 492 x 185	790 x 710 x 299
Weight (Kg)	8.2	8.4	8.4	15.4	16.3	16.3	16.8	23.8 23.7	24.3 24.2	24.4	70.3 69.9
Power consumption (W) normal / eco	293 / 223	345 / 258	345 / 258	367 / 310	431 / 366	535 / 452	535 / 452	864 / 633	1083 / 773	1301 / 899	2325 / 1511



<sup>1</sup>With ELPLM08 - not supplied. <sup>2</sup>With ELPLM15 - not supplied. <sup>3</sup>With ELPLM12 - not supplied.

<sup>4</sup> 2001 to 2021, 500-lumen and above, excluding screenless TVs, Futuresource Consulting – Quarterly Projector Market Insights – Worldwide Analyser CY21Q4.

<sup>5</sup>Special order only.

# Lens options for installation, rental and staging



Model	ELPLX03	ELPLR05	ELPLU05	ELPLW07	ELPLM12	ELPLM13	ELPLM14	ELPLL09	ELPLL10
EB-L30000U	Ratio: 0.35:1	Ratio: 0.63:1	Ratio: 0.90 - 1.09:1	Ratio: 1.29 - 1.76:1	Ratio: 1.74 - 2.35:1	Ratio: 2.28 - 3.46:1	Ratio: 3.41 - 5.12:1	Ratio: 4.79 - 7.20:1	Ratio: 6.96 - 10.45:1
Lens shift V / H	+ 25% / ± 15%	± 15% / ± 5%	± 55% / ± 25%	± 65% / ± 30%	± 65% / ± 30%	± 65% / ± 30%	± 65% / ± 30%	± 55% / ± 25%	± 55% / ± 25%



Model	ELPLX01WS ELPLX01S	ELPLX02WS ELPLX02S	ELPLU03S	ELPLU04	ELPLW05*	ELPLW08	ELPLW06	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
EB-PU1006 through to EB-PU1008	Ratio: 0.35:1	-	Ratio: 0.65 - 0.78:1	Ratio: 0.87 - 1.05:1	Ratio: 1.04 - 1.46:1	Ratio: 1.18 - 1.66:1	-	Ratio: 1.44 - 2.32:1	Ratio: 2.16 - 3.48:1	Ratio: 3.32 - 5.06:1	Ratio: 4.85 - 7.38:1	Ratio: 7.21 - 10.11:1
Lens shift V / H	+ 17% / ± 10%	-	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	-	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%
EB-PU2010 through to EB-PU2220	-	Ratio: 0.35:1	Ratio: 0.48 - 0.57:1	Ratio: 0.64 - 0.77:1	Ratio: 0.77 - 1.07:1	Ratio: 0.86 - 1.2:1	Ratio: 1.19 - 1.62:1	-	Ratio: 1.57 - 2.56:1	Ratio: 2.42 - 3.71:1	Ratio: 3.54 - 5.41:1	Ratio: 5.27 - 7.41:1
Lens shift V / H	-	+ 25% / ± 15%	+ 24% / ± 10%	± 60 / ± 18%	± 24% / ± 10%	± 60% / ± 18%	± 60% / ± 18%	-	± 60% / ± 18%	± 60% / ± 18%	± 60% / ± 18%	± 60% / ± 18%

\*ELPLW05 brightness is limited to maximum 12,000 lumens.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.