## **ESSENTIAL+ SERIES IN118BB**





## 1080p - 3400 \* - 16:9 Aspect Ratio

The IN118BB projector does more with ultra-long lamp life, high brightness, and amazing connectivity. Beam more perfect images and engage your audience with 2 HDMI inputs, VGA, video, and audio capability. Plus, the compact design and lightweight makes it as easy to move around as it is to install.

#### **Features**

## **Low Latency Gaming Mode**

Improved communication time from the input source to your projector allows for an enhanced gaming experience.

#### **USB-A Power for Devices**

Power your external devices like Amazon Firestick or Roku with the convenient USB-A input right on the projector.

## **Industry-leading Lamp Life**

The Genesis Series features up to an unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace, these projectors are an unbeatable value.

### **High Brightness**

Get better, brighter images on any surface, in any light. The Genesis Series has up to 3800 lumens.

# **Advanced Digital Image Correction**

With the new digital edge masking and image shift features – we make getting those final image adjustments perfect.

#### Zoom

The zoom ratio adds flexibility for installations using pre-existing mounts. Adjust the zoom to create the perfect image in the same space.

### **Image**

Projection Technology Texas Instruments DLP®

Panel Size 0.47" DMD

Native Resolution 1080p Full HD

Pixels 1920x1080

Aspect Ratio 16:9

Contrast Ratio 30000:1

ess (Lumens) 3400

Light Source **UHP Lamp** Light Source Life Maximum Hours 15000 Maximum Supported Resolution 1920 x 1200 31.469 ~ 97.551 Horizontal Sync. Range (KHz) Vertical Sync. Range (Hz) 56 ~ 85 (120 for 3D) Uniformity (%) 80 **Optical** Lens 1.1x Lens Zoom Adjustment Manual **Optional Lenses** 116% Image Offset (%) Focal Length (mm) 15.59 ~ 17.14 2.1 F-Stop Vertical Lens shift (%) Horizontal Lens shift (%) Keystone Adjustment Manual Vertical Keystone Correction ±40 Horizontal Keystone Correction **Projection Factor** 1.47:1 ~ 1.62:1 Projection Distance (Meters/Feet) 1.0 ~ 9.8 / 3.2 ~ 32.1 Optical Zoom 1.1:1 Digital Zoom Demagnification / Magnification  $0.8x \sim 2.0x$ Focus Adjustment Connectivity Inputs **✓** Mini D-sub 15-pin (VGA) Composite Video S-Video **✓** HDMI™ 1.4 **/ /** HDMI™ 2.0 USB-B 2.0 RJ45 - LAN 10/100/1000 3.5 mm Stereo Mini Jack **/** 3.5 mm Stereo Mini Jack with Microphone Outputs Mini D-sub 15-pin (VGA) 3.5 mm Stereo Mini Jack Powered USB-A for Wireless Dongle 3D Sync Other RS232 **✓ RJ45 HDBaseT** or 3D Formats **✓** 2.0 for Service د

USB-A for Service

Micro USB for Service

Document Reader

Video Player

Photo Viewer

Music Player

12v Screen Trigger

#### **Power**

Power Supply 100-240 V AC; 50 ~ 60 Hz

Power Consumption Max (W) 267

Power Consumption Min. (W) 210

Power Consumption Network Standby (W) 
Power Consumption Standby (W) <0.5

#### General

Dimensions (W x H x D) (mm / in) 236 x 313 x 107 / 9 x 12 x 4

Product Weight (Kilograms/Pounds) 2.6 / 5.7

 Fan Noise (dB)
 30

 Audio (W)
 10

Operating Temperature (Celsius/Fahrenheit) 5 ~ 40 / 41 ~ 104

Operating Humidity (%) 10 ~ 85

Max Operating Altitude (meters / feet) 3048 / 10000

Storage Temperature (Celsius/Fahrenheit) -10 ~ 60 / 14 ~ 140

Storage Humidity (%) 10 ~ 85

Security Kensington Security Slot™, PIN Code Lock & Timer

In the Box VGA Cable, Power Cord, Remote Control (No Batteries)

Safety and Regulatory CB, CE, EAC, cTUVus, CCC, FCC, UKCA, NOM, PSB, BIS

Environmental WEEE, EU RoHS, China RoHS, CEL, CECP

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.