

# S371

Bright projection



- **Bright SVGA projector – 3800 ANSI lumens**
- **Easy connectivity – HDMI, VGA, USB power**
- **Clear, powerful audio - 10W speaker**
- **Lightweight and portable**

Project bright and vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S371 boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.



## Specifications

|                                |  |
|--------------------------------|--|
| <b>Display/image</b>           |  |
| Display technology             | DLP  |
| Resolution                     | SVGA (800x600)   |
| Brightness                     | 3,800 lumens   |
| Contrast ratio                 | 25,000:1   |
| Native aspect ratio            | 4:3  |
| Aspect ratio - compatible      | 16:9   |
| Keystone correction - vertical | +/-40°   |
| Horizontal scan rate           | 15.38 ~ 91.15Khz   |
| Vertical scan rate             | 50 ~ 85(120 for 3D)Hz  |
| Uniformity                     | 75%  |
| Screen size                    | 0.71m ~ 7.73m (27.78" ~ 304.4") diagonal   |
| <b>Lamp info</b>               |  |
| Light source type              | Lamp   |
| Lamp watts                     | 203  |
| Lamp life hours (up to)        | 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)  |
| <b>Optical</b>                 |  |
| Throw ratio                    | 1.94:1 ~ 2.16:1  |
| Projection distance (m)        | 1m - 12m   |
| Zoom                           | 1.1  |
| Zoom type                      | Manual   |
| Focal length (mm)              | 21.85 ~ 24   |
| Native offset                  | 115%   |
| <b>Connectivity</b>            |  |
| Connections                    | <b>Inputs</b> 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm<br><b>Outputs</b> 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A<br><b>Control</b> 1 x RS232   |
| <b>General</b>                 |  |
| Noise level (typical)          | 27dB   |
| Noise level (max)              | 29dB   |
| PC compatibility               | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac   |
| 2D compatibility               | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  |
| 3D compatibility               | Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  |
| 3D                             | Full 3D  |
| Security                       | Security bar, Kensington Lock, Password protected interface  |
| OSD / display languages        | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| Operating conditions           | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m   |
| Remote control                 | Card style   |
| Speaker count                  | 1  |
| Watts per speaker              | 10W  |
| In the box                     | AC power cord<br>Remote control<br>Battery<br>Basic user manual  |
| Optional wireless models       | HDCast Pro, QuickCast Bundle, WHD200   |
| <b>Power</b>                   |  |
| Power supply                   | 100 ~ 240V, 50 ~ 60Hz  |
| Power consumption (standby)    | 0.5W   |
| Power consumption (min)        | 187W   |
| Power consumption (max)        | 225W   |
| <b>Weight and dimensions</b>   |  |
| Dimensions (W x D x H) mm      | 316 x 244 x 108  |
| Gross weight                   | 4.4 kg   |
| Net weight                     | 3 kg   |

