

X371
Bright projection









- Bright XGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker
- · Lightweight and portable

Project bright and vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the X371 boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.



This projector is easy to connect to with multiple inputs, a built-in speaker and USB power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings or classes with the optional carry bag (sold separately).

Specifications

EAN: 5055387664876, Colour: Black Display/image Display technology DIPTM Resolution XGA (1024x768) Brightness 3,800 lumens Contrast ratio 25,000:1 Native aspect ratio 4.3 Aspect ratio - compatible 16:9 +/-40° Keystone correction - vertical 15.38 ~ 91.15Khz Horizontal scan rate 50 ~ 85(120 for 3D)Hz Vertical scan rate Uniformity 75% Screen size 0.71m ~ 7.73m (27.78" ~ 304.4") diagonal Lamp info Light source type Lamp Lamp watts 203 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to) Optical 1.94:1 ~ 2.16:1 Throw ratio Projection distance (m) 1m - 12m Zoom 1.1 Zoom type Manual Focal length (mm) 21.85 ~ 24 115% Native offset Connectivity Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 General Noise level (typical) 27dB Noise level (max) 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D

 2D compatibility
 NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576k/p, 720p(50/60Hz), 1080)(50/60Hz), 1080)(50/60Hz), 1080)(50/60Hz)

 3D compatibility
 Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

 3D
 Full 3D

 Security
 Security bar, Kensington Lock, Password protected interface

 OSD / display languages
 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

 Operating conditions
 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 10W

 In the box
 AC power cord Remote control Battery

 Residue or manus

Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200

 Power
 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 187W

 Power consumption (max)
 225W

 Weight and dimensions

 Dimensions (W x D x H) mm
 316 x 244 x 108

 Gross weight
 3.58 kg

 Net weight
 3.04 kg





