

MW826ST 3400lms WXGA Education

Advanced Interactive Instruction for Leading Schools

- Short-throw ratio
- DLP technology for long-lasting picture perfection
- PointWrite Interactive Solution Compatible

Contact Us



MW826ST

[Overview](#)[Specifications](#)[Q&A](#)[Downloads](#)[Video](#)[Contact Us](#)

All Specifications

Marketing

Product Features

0.49 T/R,3D,SmartEco,LampSave,LAN control,HDMI, HDMI/MHL, PointWrite,Digital Shrink 0.75x

Display

Native Resolution

WXGA (1280x800)

Native Aspect Ratio

16:10

Brightness (ANSI lumens)

3400

Contrast Ratio (FOFO)

20000:1

Selectable Aspect Ratio

16:10,16:9,4:3,Auto,Real

Display Color

30 Bits (1,07 billion colors)

Light Source

Lamp

Light Source Wattage

200W

Light Source Life

ECO 10000 hrs,LampSave 15000 hrs,Normal 5000 hrs,SmartEco 10000 hrs

Optical

Throw Ratio

0.49

Zoom Ratio

Fixed

Lens

F/# = 2.6,f = 6.9 mm

Projection Offset (Full-Height)

105%

Keystone Adjustment

1D, Vertical \pm 30 degrees

ANSI Uniformity (Min.)

-55%

Clear Image Size

70"~120"

Image Size

70"~120"

Picture

Picture Modes

3D,Bright,Cinema,Presentation,sRGB,User 1,User 2

Color Wheel Segment (Lamp)

6 segment (RGBYCW)

Color Wheel Speed

2X (50Hz),2X (60Hz)

Compatibility

HDTV Compatibility

1080i,1080p,480i,480p,576i,576p,720p

Video Compatibility

NTSC,PAL,SECAM

3D Compatibility

Frame Packing,Frame Sequential,Side by Side,Top Bottom

[TOP](#)

MW826ST	Overview	Specifications	Q&A	Downloads	Video	Contact Us
---------	----------	-----------------------	-----	-----------	-------	------------

Monitor out (D-sub 15pin)	1
Composite Video in (RCA)	1
S-Video in (Mini DIN 4pin)	1
HDMI in	2,HDMI-1 (1.4a/HDCP1.4),HDMI-2 (1.4a/HDCP1.4/MHL)
LAN (RJ45)	1
USB Type A	1,USB Type A-1 (2.0/Power Supply1.5A)
USB Type Mini B	1,USB Type Mini B-1(service/Page up&down)
RS232 in (DB-9pin)	1

Audio

Audio L/R in (RCA)	1
Audio out (3.5mm Mini Jack)	1
Audio in (3.5mm Mini Jack)	2

Environment

Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	260
Acoustic Noise (Typ./Eco.)(dB)	33/29
Operating Temperature	0~40°C

Accessories

Carry Bag	Yes,5J.J3T09.001 (optional)
Remote Control w/ Battery	RCE013
Power Cord (by region)	1 (3.0M)
User Manual CD	1 (24L)
3D Glasses	(Optional),Yes, DGD5
Quick Start Guide	1 (18L)
Warranty Card (by region)	Yes
Anti-dust Filter	(Optional),Yes
Wall Mount	(Optional),Yes, WM06G3

OSD

OSD Language	30L
--------------	-----

Smart System

TOP

MW826ST	Overview	Specifications	Q&A	Downloads	Video	Contact Us
---------	--------------------------	---------------------------------------	-------------------------	---------------------------	-----------------------	----------------------------

Zoom Ratio	Fixed
Lens Control	Manual Focus
Keystone Correction	1D, Vertical \pm 30 degrees
Projection Offset**	105%
Projection Size (Diagonal)	70"-120"

Display

Projection System	DLP Single 0.65" WXGA
Resolution	1280x800 pixels
Brightness	3,400 ANSI Lumens
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Lamp (200W)
Light Source Life*	5000/10000/10000/15000 hours (Normal/Eco/SmartEco mode/Lampsave)
Contrast Ratio	20,000:1
DMD Type	DC3 DMD Chip

Audio

Built-in Speaker	10Wx1
------------------	-------

Special Feature

Security Lock	Kensington Lock Security Bar
---------------	---------------------------------

Connectivity

I/O Port	HDMI x 2 (HDMI-2 share with MHL) PC In (D-sub 15pin) x 2 (share with component video) Monitor Out (D-sub 15pin) x 1 Composite Video In (RCA) x 1 S-Video In x 1 Audio In (mini jack) x 2 Audio L/R In (RCA) x 1 Audio Out (mini jack) x 1 LAN RJ45 x 1 (LAN control) RS232 (DB-9pin) x 1 USB (type A) x1 (power only 5V/1.5A) USB (type mini B) x 1 IR Receiver x2 (front, top)
----------	---

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
--------------------	--

[TOP](#)

MW826ST	Overview	Specifications	Q&A	Downloads	Video	Contact Us
HDTV Compatibility						480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility						NTSC, PAL, SECAM
Power						
Power Consumption (Max/Normal/Eco)						Typical 260W
Standby Power Consumption						Network Standby<2W, Standby<0.5W
Dimension and Weight						
Product Dimensions (WxHxD)						296*120*239 mm
Product Weight						2.6 Kg (5.7 lbs)
Operation Condition						
Operating Temperature						0° ~ 40°C
Noise Level (Normal/Eco)						33/29dBA
Accessories						
Accessories (Standard)						Remote Control w/ Battery RCE013 x 1 Power Cord (by region) x 1 Quick Start Guide x 1 User Manual CD x 1 Warranty Card (by region) x 1 Spare Lamp Kit 5J.JGE05.001 Dust Filter 5J.JGV14.001
Accessories (Optional)						3D Glasses DGD5 5J.J9H25.002 Document Camera S30 9H.J9L78.T3E PointWrite Kit PW02 5J.J9A26.12E PointWrite Touch Module PT12 5J.J8L26.13E Wall Mount 5J.J4R10.011
OSD						
On Screen Display Language						Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)
LS2LT1						
Lens						F/#=2.6, f=6.9mm
InstaShow Host						
Power Supply						AC100V to 240V, 50Hz to 60Hz