

ZX350ST

Ultra-compact high brightness laser projector









- Bright XGA DuraCore laser projector 3300 lumens and IP6X certified
- Ultra compact and short throw lens for easy installation - 360-degree and portrait projection
- DuraCore laser technology 30,000 hours maintenance-free laser light source
- Designed with the environment in mind -DuraCore laser technology cuts power consumption and ensures a long product lifespan



The ZX350ST is one of Optoma's most compact and hassle-free XGA DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 3300-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

Specifications

EAN: 5055387666771, Colour: White

UPC: 796435 44 640 6, Colour: White Display/image

DLP™ Display technology Resolution XGA (1024x768) **Brightness** 3.300 lumens Contrast ratio 300,000:1 Native aspect ratio 4:3 4:3,16:9 Aspect ratio - compatible Keystone correction - vertical +/-40° Has vertical auto keystone Yes

correction

1073.4 Displayable colours (millions) Horizontal scan rate 15 ~ 140Khz 24 ~ 120Hz Vertical scan rate Uniformity 75%

0.81m ~ 7.62m (32" ~ 300") diagonal Screen size

Lamp info Light source type LASER life 30,000 hours Ontical

Throw ratio 0.617:1 Projection distance (m) 0.4m - 3.76m Zoom type Fixed 21.85 ~ 24.01 Focal length (mm) 115%

Native offset Connectivity

3D

Connections Inputs 2 x HDMI 1.4a 3D support

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General Noise level (typical) 32dB Noise level (max) 34dB

FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 2D compatibility

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) 3D compatibility

Full 3D

Security Security bar, Kensington Lock, Password protected interface

IP rating

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

Remote control Card style Speaker count 15W Watts per speaker AC power cord In the box 2x AAA batteries

Basic user manual UHDCast Pro

Optional wireless models

Power 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) < 0.5W Power consumption (min) 98W 139W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) mm 274 x 216 x 114 Gross weight 4.2 kg Net weight 3 kg





