

DW855 MULTIMEDIA PROJECTORS



DW855 is a Compact, Portable, High Brightness Projector with Stunning Colors and Diverse Connectivity

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 5,500 lumens high brightness with 4,000 hours lamp-life in Eco Mode
- Easy image corrections with 4 corner geometric adjustment, horizontal and vertical keystone corrections
- 1.2x zoom ratio for installation flexibility
- Power over USB-A (5V/1.5A) enables connection of HDMI based multimedia or NovoConnect wireless collaboration devices: NC-X300 and NovoPro
- New On-screen display (OSD) control menu for ease of use and improved control over viewing options
- viviBlack enhances black level for higher contrast ratio
- Supports network control









DW855 projector is suited for installations in meeting rooms for professional usage

The DW855 projector brings outstanding performance with its WXGA resolution and a high degree of vibrancy thanks to 5,500 lumens of brightness and a contrast ratio of 15,000:1. With a weight of 3.4 kg and a flexible 1.2x zoom ratio it allows for easy carrying between different meeting rooms, and is ideal for taking on the road. With advanced color technology, multiple modes and hardware features the projector provides lasting, reliable and precise colors, it is offering the optimum picture performance for any use in many environments.



DW855

SPECIFICATIONS

| Image | Display Type | Single chip DLP® Technology by Texas Instruments |
|---------------|---------------------------|---|
| | Brightness | 5500 ANSI Lumens |
| | Native Resolution | WXGA (1280 x 800) |
| | Max. Supported Resolution | WUXGA (1920x1200)@60Hz |
| | Contrast Ratio | 15,000:1 |
| | Native Aspect Ratio | 16:10 |
| | Keystone Correction | +/- 30 Degree; +/- 30 Steps |
| Optical | Throw Ratio | 1.6- 1.92 |
| | Image Size (Diagonal) | 25.3" - 317.99" |
| | Projection Distance | 1.2 - 10 m |
| | Projection Lens | F=2.42 - 2.97 , f=20.70 - 31.05 mm |
| | Zoom Ratio | 1.2x |
| | Offset | 114.9% +/- 5% |
| | Lens Shift Range | 24-30 Hz, 47-120 Hz |
| | Focus | Manual |
| Features | Features | 3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), Keypac lock |
| Compatibility | Video | SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L) |
| Connectivity | I/O Connection Ports | VGA-In (15pin D-Sub), HDMI Number of Ports 1.4a (2x), Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, 12v Trigger (Ø3.5mm mini jack), RS-232, USB A (2x (5V/ 1.5A) (Power Only), USB miniB (Service) |
| General | Lamp Life and Type | 3,000/4,000/5,000 Hours (Normal/ Eco./Dynamic Eco), 310W/250W |
| | Speakers | 10W (Mono) |
| | Dimensions (W x D x H) | 314 x 213 x 126 mm |
| | Weight | 3.4 kg |
| | Noise Level | 36dB /31dB (Normal/Eco. Mode) |
| | Power | AC 110-240V, 50/60Hz |
| | Warranty | Standard Warranty: 3 years projector / 1 year on lamp or 1.000 hours whichever comes first |
| | Standard Accessories | VGA Cable, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord |
| | Optional Accessories | Spare Lamp P/N (SS-5811126482-VV), Remote Control P/N (5042149001) |
| | UPC Code | 813097 024763 |