EB-L570U

5,200 lumens brightness fixed lens laser projector, an ideal use for education, businesses and visitor attractions environments.

Exceed your vision with Epson compact 3LCD technology laser projector, delivers sharp and smooth 4K images. The EB-L570U delivers effective, practical and creative display applications across a number of different industries.

Incredible picture quality

Providing higher quality content output, more engaging and impactful displays even in brightly-lit environments, the EB-L570U offers impressive 5,200-lumen brightness, 4KE resolution and lens shift at an affordable price. The EB-L570U is also a scalable display from 50 to 500-inches.

Superior connectivity

This displays solution offers many ways to connect. BYOD connectivity with optional wireless or wired and HDBaseT. Offers MTR auto power-on function by HDMI signal detection. The EB-L570U comes equipped with future-proofed connectivity options including HDMI, HDBaseT and built-in media player. Compatible with iProjection software for easy connectivity with mobile devices and content sharing.


Effortless and flexible installation

360-degree installation without compromising the display quality and supports 21:9 and 16:6 ultra-widescreen, lens shift and HDMI output. For projector installs offers premium multi-projection features - options that you would normally expect to see in higher range or priced models. Edge blending combined optional ELPEC01 camera enables simple stacking/ tiling features.

Peace of mind and long-lasting durability

Project for longer with exceptional reliability and a longer usage life of up to 30,000 hours in Eco Mode (20,000 hours normal).

DATASHEET / BROCHURE



KEY FEATURES

- 5,200-lumen brightness Sharp images and vivid colours, even in well-lit rooms
- 4KE resolution Sharp 4KE images for excellent clarity
- BYOD connectivity with optional wireless or wired and HDBaseT
- Effortless, flexible installation Compact with wide lens shift and multiprojection functions
- Large image Scalable display size of up to 500 inches





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0,67 inch with C2 Fine
IMAGE	
IMAGE Color Light Output	5.200 Lumen- 3.640 Lumen (economy) In accordance with IDMS15.4
White Light Output	5.200 Lumen - 3.640 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WUXGA
High Definition	4K enhancement
Aspect Ratio	16:10
Contrast Ratio	Over 2.500.000 : 1
Light source	Laser
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Colour Video Processing	10 Bits
Colour Reproduction	Upto 1.07 billion colours
HDR support	HDR10
OPTICAL	
Throw Ratio	1,35 - 2,20:1
Zoom	Manual, Factor: 1 - 1,6
Lens	Optical
Lens Shift	Manual - Vertical ± 50 %, horizontal ± 20 %
Screen Size	50 inches - 500 inches
Projection Distance Wide Projection Distance Tele	1,4 m - 14,8 m 2,4 m - 23,8 m
Projection Distance Vide/Tele	
Projection Lens F Number	1,5 - 1,7
Projection Lens Focal Length	
Projection Lens Focus	Manual
CONNECTIVITY Interfaces	USB 2.0-A, USB 2.0 Type B (Service Only), RS-232C, HDMI in (2x), HDMI out, HDBaseT
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv6, SNMP, PJLink
Security	Kensington lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection
2D Colour Modes Other features	Dynamic, Natural, Cinema, Presentation, DICOM SIM 21:9 aspect ratio support, 4K enhancement, A/V mute, Arc Correction, Auto source search,
Other leatures	Built-in speaker, Direct Power on/off, Document Camera Compatible, Edge Blending, PC Free
	Super resolution, Ultra-wide display (16:6), iProjection App
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector control	via: Crestron, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery
	Control4 Simple Device Discovery Protocol
GENERAL	
GENERAL Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	440 x 304 x 122 mm (Width x Depth x Height)
Product weight	8.3 kg
Noise Level	Normal: 31 dB (A) - Economy: 23 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	Epson Projector Management
	Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker,
Options	
Options	Safety wire set, Visualiser camera, WP System - ELPWP20
Loudspeaker	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt
	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection
Loudspeaker Room Type / Application	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Loudspeaker Room Type / Application Positioning	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop
Loudspeaker Room Type / Application	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Loudspeaker Room Type / Application Positioning	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop
Loudspeaker Room Type / Application Positioning Colour	Safety wire set, Visualiser camera, WP System - ELPWP20 10 Watt Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop

EB-L570U

WHAT'S IN THE BOX

- Cable cover
- Main unit
- Remote control incl. batteries

EPSON[®]

- User guide
- Warranty Documents

OPTIONAL ACCESSORIES

- Air Filter ELPAF56 L600/EB-14XX Series V13H134A56
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Camera Unit ELPEC01 V12HA46010
- Screen (80" Mobile X type16:9) ELPSC21 V12H002S21
- Screen (80" Multi-Aspect) ELPSC26 V12H002S26

LOGISTICS INFORMATION

ѕки	V11HA98080
EAN code	8715946714912
Country of Origin	Philippines
Layer	2 Units

TEKSEL d.o.o. Tržaška cesta 132 1000 Ljubljana Tel.: +386 1 620 77 25 Faks: +386 1 620 77 26 Spet: www.teksel.si E-pošta: info@teksel.si

Blagovne znamke ali registrirane blagovne znamke so last podjetja Seiko Epson Corporation ali njihovih lastnikov. Informacije o izdelkih se smejo spremeniti brez vnaprejšnjega opozorila.

EB-L570U

