

**SHURE**

Specifications

Frequency	2402 to 2480 MHz
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
RF Output Power	-1.18 dBm EIRP (Left), 1.99 dBm EIRP (Right)
Antenna Type	Antenna Diversity
Antenna Gain	-4.32 dBi (Left), -2.73 dBi (Right)
Supported Codecs	Qualcomm aptX™, SBC, AAC
Working Range	10 m
Operating Temperature	0°C to 45°C (32°F to 113°F)
Charging Temperature Range	0°C to 45°C (32°F to 113°F)
Storage Temperature	-10°C to 35°C (14°F to 95°F)
Transducer Type	Single Dynamic MicroDriver
Sensitivity	at 1 kHz 107 dB SPL/mW
Impedance	at 1 kHz 20 Ω
Noise Attenuation	up to 37 dB
Frequency Range	21 Hz–17.5 kHz
Input Connector	MMCX connectors
Net Weight	20.8 g (.7 oz.)

Shure Europe GmbH

Headquarters Europe, Middle East, Africa, Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12 | 75031 Eppingen, Germany
Phone: +49 (0)7131 72 14 -111 | Fax: +49 (0)7131 72 14 -168