

# SHURE

## Specifications

- **Sensitivity at 1 kHz:** 114 dB SPL/mW
- **Impedance at 1 kHz:** 9  $\Omega$
- **Noise Attenuation:** up to 37 dB
- **Frequency Range:** 15 Hz–20 kHz
- **Input Connector:** MMCX connectors
- **Net Weight:**
- **Operating Temperature:** 0°C to 45°C (32°F to 113°F)
- **Storage Temperature:** -10°C to 35°C (14°F to 95°F)
- **Colour:** jade



## Features

- Four high-definition drivers offer unparalleled high-end clarity and low-end performance
- Groundbreaking low-pass filter provides the deep low-end performance of a true subwoofer
- Sound Isolating design blocks up to 37dB of external noise for truly immersive listening
- Rugged build with sweat-resistant construction to withstand almost all environments
- Adjustable frequency response thanks to interchangeable nozzle inserts
- Nozzle inserts provide an Extended (+2.5 dB, 4 kHz to 12 kHz) Balanced (neutral), Bright (+2.5dB, 1kHz to 8kHz), or Warm (-2.5dB, 1kHz to 8kHz) sound signature
- Detachable cable provides multiple connectivity options for long-term device compatibility, upgrades, and easy maintenance
- Secure over-the-ear configuration ensures super secure fit whilst keeping cable out of the way for unmatched long-wearing comfort
- Comes complete with a plethora of additional accessories for the ultimate in sonic personalisation, fitment, and long-term reliability
- Comes with detachable a RMCE UNI Cable with built-in microphone and controls - compatible with iOS and Android