

SHURE

Features

- Up to 8 selectable channels
- Up to 4 compatible systems*
- Antenna Switching Diversity
- Adjustable Squelch Level
- 1/4" and XLR output
- Available with Handheld and Lavalier system packages



Technical Specifications

- Power Supply: 12 to 18 V DC @ 220 mA, supplied by external power supply
- Maximum Output Level: XLR connector into 100 k Ω load: -16 dBV, 6.35 mm (1/4") connector into 100 k Ω load: -22 dBV mW

Further Technical Specifications

- Dimensions: 32 mm X 168 mm X 104.5 mm (1.26 in. x 6.625 in. x 4.2 in.)
- Weight: 245 g (11.5 oz.)
- Housing: Molded ABS
- Audio Output Level (Ref. \pm 48 kHz deviation with 1 kHz tone):
- XLR connector into 100 k Ω load: -16 dBV (MIC)
- 6.35 mm (1/4") connector into 100 k Ω load: -22 dBV (MIC)
- Output Impedance:
- XLR connector: 600 Ω
- 6.35 mm (1/4") connector: 600 Ω
- Sensitivity: -105 dBm for 12 dB SINAD, typical
- Image Rejection: >50 dBm, typical
- Power Requirements: 12 to 18 V DC @ 130 mA, supplied by external power supply

Shure Europe GmbH

Headquarters Europe, Middle East, Africa, Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12 | 75031 Eppingen, Germany
Phone: +49 (0)7131 72 14 -111 | Fax: +49 (0)7131 72 14 -168