

# SHURE



## Specifications

Wireless Technology	Digital UHF
Number of RF Channel Frequencies	1760
Diversity	Antenna Diversity
Available RF Frequency Bands	H50: 534-598MHz, G50: 470-534MHz
RF Bandwidth	44 MHz
Frequency Step Size	25 kHz
RF Channel Scanning	Auto-Scan
Max Operating Range	328.1' (100m)
Max Transmitters per Band	60
Latency	< 2.9 ms
Receiver Type	Tabletop
Audio I/O	1x XLR 3-Pin Male Balanced Output 1x 1/4" TRS Female Balanced Output
Audio Output Level	XLR Output: +18 dBV (Line Level)
	XLR Output: -12 dBV (Mic Level)
	1/4" Output: +12 dBV (Consumer Level, Instrument Level)
Frequency Response	30 Hz to 20 kHz +/-1 dB (Dependent on Mic)
Network I/O	1x RJ45 (10/100 Mb/s)
Approximate RF Sensitivity	-98 dBm
Power Requirements	AC/DC Power Adapter
AC/DC Power Adapter	15 VDC at 600 mA (Included)
Display & Indicators	1x Backlit LCD (Battery Status, Channel, Group, Menu Navigation) 2x Multi-Segment LED (AF Level, Output Level, Peak)
USB/Lightning Connectivity	None
Dimensions	10.1 in. x 2.0 in. Length x Dia.
Weight	32 oz (907.18g)