HANNspree

HO 101 HTB 10.1" Open Frame Touch Monitor

Experts in **Display**

Open Frame Touch Monitor HO 101 HTB

25,65cm / 10.1" Diagonal LED Backlight – Format 16:10

- 1280 x 800 Resolution
- 10-Point Touch P-Cap Technology
- 170° / 170° Ultra Wide Viewing Angle
- Dual Input: HDMI + VGA
- IP54 (front) Rating Level
- 12 Volt External Power Supply
- ≥6H Toughened Hard Panel Surface
- TP Module Thickness 2mm
- Touch-Through Glass (available upon request*)
- Sturdy Metal Case
- Orientation: Landscape, Portrait, Face-Up











25,65 cm / 10.1"

Part. No..: HO 101 HTB

SIZE, RESOLUTION

10.1"

10.1"

16:10 Aspect Ratio



1280 x 800

CONNECTIVITY, IP LEVEL



HDMI VGA



IP 54 Water & Dust Protection

VIEWING ANGLE, HARD GLASS



170° Wide Viewing Angle



Hard Glass Display Protection

OTHER FEATURES



10 Points Touch



Touch to USB Link

Technical Specifications >>>

* For more details contact your local HSP office / representative or send us a request via the product enquiry form on the website.


HANNspree


HO 101 HTB 10.1" Open Frame Touch Monitor

Experts in **Display**

Display Size	25,65 cm / 10.1" Diagonal	
Panel Type	TFT – LED Backlight, IPS Panel (*)	
Aspect Ratio	16:10	
Resolution (H x V)	1280 x 800	
Brightness	350 cd/m² (Panel) – 300 cd/m² (Monitor)	
Contrast (Typ.)	800:1 (Typical)	
Viewing Angle L/R; U/D	170° H / 170° V (CR >10)	
Response Time	25 msec (Typ.)	
Pixel Pitch	0,1695 (H) x 0,1695 (V) mm	
Touch Type	Projected Capacitive Type – 10-Point Touch Material Glass + Glass (G+G)	
Display Colors	16,7M Colors	
Display Protection	Thickness 2 mm	
Hardness / Transmittance	≥6H Toughened hard panel surface / ≥85%	
IP Rating Level	IP 54 (Front), Water and Dust Protection *	
Horizontal Frequency	30 ~ 55 kHz	
Vertical Frequency	56 ~ 60 Hz	
External Power Adapter	DC: 12Volt / 3A	
Input 1	VGA (D-Sub)	
Input 2	HDMI	
Input 3	USB Type B (for Touch function)	
Speakers		
Power Consumption	On: 5W; Stand-by: 0,2W; Off: 0,2W	
Product Dimensions	310,6 x 34,8 x 188,6 mm (W x D x H)	
Packing Dimensions	370 x 90 x 237 mm (W x D x H)	
Net / Gross Weight	1,9 Kg / 2,6 Kg	

VESA Mounting	-
Controls	Power, Auto, (+), (-), Menu
Color	9300, 7500, 6500, User Mode
Preset Mode	N/A
On Screen Display	9 OSD Languages
LED Backlight life	20000 hours
Accessory	Power Adaptor; EU Power Cord (1,8m); USB Cable (1,8m); HDMI Cable (2m)
Orientation	Landscape, Portrait, Face-Up





Supplier's Name	HANNspree
Model Name	НО101НТВ
Energy efficiency class for standard Dynamic Range (SDR)	С
Annual Energy Power Consumption (kWh/1000h)	5 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	5 W
Off mode power demand (W)	0,2 W
Standby mode power demand (W)	0,2 W
Screen Diagonal (cm / inches)	25,65cm/10.1"
Resolution	1280 x 800

PART. NO.: HO101HTB



^{**} IP54: The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

Display Solutions

^{* &}quot;IPS" word mark / trademark and related patents on technologies belong to their respective owners.

HO 101 HTB 10.1" Open Frame Touch Monitor



HANNspree

HO 101 HTB 10.1" Open Frame Touch Monitor

Experts in **Display**

