

NEC MultiSync® C750Q
LCD 75" Midrange Large Format Display

Datasheet



Stunning visibility for presentations and digital signage

Enhance your meeting and conferencing performance with stunning UHD resolution. Get high-end quality and reliability at a low total cost of ownership with long life-times.

Professional haze levels ensure great visibility without distracting reflections - along with brightness of up to 350 cd/m², the NEC MultiSync C Series meets the demands of today's meeting environments. Slim bezels and a modern appearance complement state of the art architecture to integrate perfectly into interior designs. With embedded office functionalities, start up ad-hoc meetings without the hassle of setting up the display environment first. Wake-up on connection is just one of many features which make meetings more efficient.

With the NEC MultiSync C750Q, presenters will feel confident during meetings of up to 12 participants whilst retailers and hospitality facilities can boost sales through digital signage.

Benefits

Future Ready with Open Modular Intelligence Expansion - upgrade the power of your display at any time by seamlessly integrating one of Sharp/NEC's options for OPS Slot-in PCs or signal interfaces for content feed and computing.

Mission-critical 24/7 ready operation - the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Ease of use and operation - smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

Cost Saving Device Management - save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Future-proof signal connectivity and processing - numerous native UHD resolution inputs with 60Hz refresh rate including DisplayPort and HDMI, plus automatic upscaling to UHD for other signals, provide "pixel-free viewing" on a large scale.

Product Information

Product Name	NEC MultiSync® C750Q
Product Group	LCD 75" Midrange Large Format Display
Order Code	60005460

Display

Panel Technology	IPS with Edge LED backlights
Active Screen Area (W x H) [mm]	1,649.7 x 927.9
Screen Size [inch/cm]	75 / 189
Brightness [cd/m ²]	350, 250 (shipment setting)
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	Pro (28)
Supported Orientation	Landscape; Portrait

Resolution

Native Resolution	3840 x 2160
Supported Resolutions	1920 x 1080; 1920 x 2160; 3840 x 2160; 4096 x 2160

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1
Vertical Frequency [Hz]	24 - 85

Connectivity

Input Video Digital	1 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)
Input Audio Digital	1 x DisplayPort; 2 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Input Data	1 x USB 2.0 (MediaPlayer)
Output Audio Analogue	1 x 3,5 mm jack
Input Detect	Custom; First; Last

Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
OPS Max. Current / Power Consumption [A / W]	4.7 / 75

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Human Sensor	Optional, external, 4-5m range, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption [W]	195 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC

Environmental Conditions

Operating Temperature [°C]	+0 to +40
----------------------------	-----------

Operating Humidity [%]	20 to 80
------------------------	----------

Mechanical

Dimensions (W x H x D) [mm]	Without stand: 1,681 x 960 x 71
-----------------------------	---------------------------------

Weight [kg]	53
-------------	----

Bezel Width [mm]	14.8 (left and right); 14.8 (top and bottom)
------------------	--

VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); 600 x 400 (FDMI); M8
--------------------	---

Ingress Protection	IP5x (front); IP2x (back)
--------------------	---------------------------

Packaging Dimensions (W x H x D) [mm]	1,830 x 1,190 x 280
---------------------------------------	---------------------

Packaging Weight [kg]	65.5
-----------------------	------

Colour Bezel	Pantone 426M (black)
--------------	----------------------

Material	Metal
----------	-------

MediaPlayer

Supported File Storage / File System	USB 2.0 / FAT16, FAT32
--------------------------------------	------------------------

Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640
-------------------------	--

Supported Video Formats	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)
-------------------------	---

Supported Audio Formats	MP3 (MP3); max. bit-rate 320 kBit/s
-------------------------	-------------------------------------

Available Options

Accessories	Feet (ST-801); Trolley (PD02MHA, PD03MHA, PDMHM-L); Wall mount (PDW T XL-2)
-------------	---

OPS Slot	HDBaseT receiver; Intel® Atom, Celeron and Core CPUs
----------	--

Green Features

Energy Efficiency	Ambient light sensor; Carbon savings meter; Energy consumption: 165 kWh/1000 h; Energy efficiency class: G; Local dimming
-------------------	---

Additional Features

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
-------------------------	---

Safety and Ergonomics	CE; EAC; EMC Class B; FCC; SASO; TÜV GS; UL/C-UL or CSA; VCCI
-----------------------	---

Pixel Failure Class	ISO 9241-307, Class 1
---------------------	-----------------------

Audio	Integrated Speakers (10 W + 10 W)
-------	-----------------------------------

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
------------------	--

Warranty	3 years warranty incl. backlight; optional 4. + 5. year warranty extension ¹
----------	---

Operating Hours	24/7
-----------------	------

External Control	AMX NetLinx Support; ASCII Control Commands; Crestron Connected; Crestron Connected; Crestron Connected; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP
------------------	--

Remote Management	Automated Email Alerts; NEC NaViSet Administrator 2
-------------------	---

Security	Disable HW Buttons; Disable IR Functionality; Emergency Notification
----------	--

¹ please refer to terms and conditions of warranty extensions



CE



TÜV GS



VCCI

This document is © 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023