

Sharp PN-HS431 LCD 43" Professional Large Format Display

Datasheet





Make a real impact - anytime, anywhere

Bring all of your information bursting into life wherever and whenever you need to stand out from the crowd.

Sharp's PN-HS professional digital signage displays offer a unique combination of an exceptionally slim and stylish design, brilliantly clear and bright 4K pictures, 24/7 operation and flexible installation. It makes them great for signage and information sharing in a wide range of retail, corporate and transport environments, including high brightness areas like train stations and airports.

Benefits

Simply more life-like - the displays come with a wide colour gamut showing every colour with much greater accuracy.

Operation around the clock - 24/7 with 700 cd/m² brightness.

Real impact - with built-in speakers, support for USB playback and range of connectivity, it is easy to create digital signage.

Control made simple – using an integrated LAN/RS-232C interface all your displays can easily be controlled and monitored from a single PC.

All the flexibility you need - the display can be wall mounted in either landscape or portrait mode as well as face-down on a ceiling or face-up on a table or floor.

Product Information

| Product Name | Sharp PN-HS431 |
|---------------|---|
| Product Group | LCD 43" Professional Large Format Display |
| Order Code | 60005551 |

Display

| Panel Technology | TFT with Direct LED backlights |
|---------------------------------|---|
| Active Screen Area (W x H) [mm] | 941 x 529 |
| Screen Size [inch/cm] | 43 / 107 |
| Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.245 x 0.245 |
| Brightness [cd/m²] | 700 |
| Contrast Ratio (typ.) | 1200:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn] | 1.073 (10bit) |
| Response Time (typ.) [ms] | 8 |
| Panel Refresh Rate [Hz] | 60 |
| Haze Level [%] | Pro (25) |
| Supported Orientation | Face Down; Face Up ¹ ; Landscape; Portrait |

Resolution

| Native Resolution | 3840 x 2160 | | | | |
|-----------------------|--------------|--------------|--------------|------------|--|
| Supported Resolutions | 1024 x 768; | 1280 x 960; | 1680 x 1050; | 640 x 480; | |
| | 1280 x 1024; | 1360 x 768; | 1920 x 1080; | 800 x 600; | |
| | 1280 x 720; | 1400 x 1050; | 3840 x 2160; | 848 x 480 | |
| | 1280 x 800; | 1440 x 900; | 4096 x 2160; | | |

Connectivity

| Input Video Analogue | 1 x VGA |
|----------------------|----------------------|
| Input Video Digital | 3 x HDMI (with HDCP) |
| Input Audio Analogue | 1 x 3,5 mm jack |
| Input Audio Digital | 3 x HDMI |
| Input Control | LAN 100Mbit; RS232 |
| Input Data | 1 x USB Medaplayer |

Electrical

| Power Consumption [W] | 140 (max.) |
|------------------------|----------------------------------|
| Power Savings Mode [W] | < 0.5; < 1 (Networked Standby) |
| Power Management | VESA DPMS |
| Power Supply | 100-240 V AC; 50/60 Hz; internal |

Environmental Conditions

| Operating Temperature [°C] | +0 to +40 |
|----------------------------|-----------|
| Operating Humidity [%] | 20 to 80 |
| Storage Humidity [%] | 10 to 90 |
| Storage Temperature [°C] | -20 to 60 |

Mechanical

| Dimensions (W \times H \times D) [mm] | 973 x 561.2 x 63.5 |
|---|--|
| Weight [kg] | 11.5 |
| Bezel Width [mm] | 13.9 (bottom); 13.9 (left and right); 13.9 (top) |
| VESA Mounting [mm] | 200 x 200 (FDMI); 4 holes; M6 |
| Packaging Dimensions (W x H x D) [mm] | 1,070 x 680 x 141 |
| Packaging Weight [kg] | 14 |

Green Features

| Energy Efficiency | Energy consumption: 115 kWh/1000 h; Energy efficiency class: G; LED backlight |
|-------------------|---|
| | |

Additional Features

| Special Characteristics | ASCII Control Commands; CEC Support; Removable Logo; Scheduler; USB Media Player |
|-------------------------|---|
| Colour Versions | Black Front Bezel, Black Back Cabinet |
| Safety and Ergonomics | CE; EAC; RoHS |
| Audio | Integrated Speakers (2 x 10 W) |
| Shipping Content | 2x AAA batteries; CD-ROM (User Guides/Manuals); Display; Logo Sticker; Power Cable; Remote Control; Setup Manual |
| Warranty | 3 years warranty incl. backlight; on-site service; optional 4. \pm 5. year warranty extension 2 |
| Operating Hours | 24/7 |
| External Control | ASCII Control Commands; HDMI CEC; Scheduled Timer |
| | |

¹ adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

² please refer to terms and conditions of warranty extensions





CE

This document is © 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023