

Sharp PN-HW501 LCD 50" Essential Large Format Display

Datasheet





Clearly a better choice. Bring content to life - fast

Enhance almost any professional environment with the outstanding 4K Ultra HD clarity of Sharp's PN-HW displays. They offer a wide range of screen sizes and flexible installation methods, including standalone operation, making them the ideal choice for both retail and corporate organisations.

With Sharp's PN-HW digital signage displays you can enjoy the perfect combination of slim and stylish design and crystal clear pictures. So you can get your message across loud and clear, wherever it needs to be seen.

Benefits

Simply more life-like - the displays come with a wide colour gamut showing every colour with much greater accuracy.

Business hours operation time - 16/7 with 350 to 400 cd/m² brightness.

Instant plug & go – with the built-in USB MediaPlayer slideshows of 4K Ultra HD photos and videos as well as music can be played, no need to connect a separate PC or other hardware.

Control made simple – using an integrated LAN/RS-232C interface all your displays can easily be controlled and monitored from a single PC.

Real impact - with built-in speakers, support for USB playback and range of connectivity, it is easy to create digital signage.

Product Information

| Product Name | Sharp PN-HW501 |
|---------------|--|
| Product Group | LCD 50" Essential Large Format Display |
| Order Code | 60005497 |

Display

| Panel Technology | TFT with Direct LED backlights |
|------------------------------------|---|
| Active Screen Area (W x H) [mm] | 1,085 x 616 |
| Screen Size [inch/cm] | 50 / 125 |
| Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.285 x 0.285 |
| Brightness [cd/m²] | 350 |
| Contrast Ratio (typ.) | 4000:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn] | 1.073 (10bit) |
| Response Time (typ.) [ms] | 8 |
| Panel Refresh Rate [Hz] | 60 |
| Haze Level [%] | Standard (2) |
| Supported Orientation | Landscape; Portrait |
| | |

Resolution

| Native Resolution | 3840 x 2160 | | | |
|-----------------------|--------------|--------------|--------------|------------|
| Supported Resolutions | 1024 x 768; | 1280 x 960; | 1680 x 1050; | 640 x 480; |
| | 1280 x 1024; | 1360 x 768; | 1920 x 1080; | 800 x 600; |
| | 1280 x 720; | 1400 x 1050; | 3840 x 2160; | 848 x 480 |
| | 1280 x 800; | 1440 x 900; | 4096 x 2160; | |

Connectivity

| Input Video Analogue | 1 x VGA |
|-----------------------|----------------------|
| Input Video Digital | 3 x HDMI (with HDCP) |
| Input Audio Analogue | 1 x 3,5 mm jack |
| Input Audio Digital | 3 x HDMI |
| Input Control | LAN 100Mbit; RS232 |
| Input Data | 1 x USB Medaplayer |
| Output Audio Analogue | 1x Cinch (L/R) |

Electrical

| Power Consumption [W] | 130 (max.) |
|------------------------|----------------------------------|
| Power Savings Mode [W] | < 0.5; < 1 (Networked Standby) |
| Power Management | VESA DPMS |
| Power Supply | 100-240 V AC; 50/60 Hz; internal |

Environmental Conditions

| Operating Temperature [°C] | +0 to +40 |
|----------------------------|-----------|
| Operating Humidity [%] | 20 to 80 |
| Storage Humidity [%] | 10 to 90 |
| Storage Temperature [°C] | -20 to 60 |

Mechanical

| Dimensions (W x H x D) [mm] 1,124 x 646 x 69 | | |
|--|--|--|
| Weight [kg] | 13 | |
| Bezel Width [mm] | 12 (left and right); 12 (top); 14 (bottom) | |
| VESA Mounting [mm] | 4 holes; 400 x 200 (FDMI); M6 | |
| Packaging Dimensions (W x H x D) [mm] | 1,238 x 795 x 185 | |
| Packaging Weight [kg] | 17 | |

Green Features

| Energy Efficiency Energy consumption: 115 kWh/1000 h; Energy efficiency class: G; LED backlight | |
|---|--|
|---|--|

Additional Features

| Special Characteristics | ASCII Control Commands; CEC Support; Removable Logo; Scheduler; USB Media Player | |
|-------------------------|---|--|
| Colour Versions | Black Front Bezel, Black Back Cabinet | |
| Safety and Ergonomics | CE; EAC; RoHS | |
| Audio | Integrated Speakers (2 x 10 W) | |
| Shipping Content | 2x AAA batteries; CD-ROM (User Guides/Manuals); Display; Logo Sticker; Power Cable; Remote Control; Setup Manual | |
| Warranty | 3 years warranty incl. backlight; on-site service; optional 4. + 5. year warranty extension 1 | |
| Operating Hours | 16/7 | |
| External Control | I Control ASCII Control Commands; HDMI CEC; Scheduled Timer | |
| | | |

¹ please refer to terms and conditions of warranty extensions



This document is $\ensuremath{\mathbb C}$ 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023