


Datasheet





Clearly a better choice. Bring content to life - fast

Enhance almost any professional environment with the outstanding 4K Ultra HD clarity of Sharp's PN-HW displays. They offer a wide range of screen sizes and flexible installation methods, including standalone operation, making them the ideal choice for both retail and corporate organisations.

With Sharp's PN-HW digital signage displays you can enjoy the perfect combination of slim and stylish design and crystal clear pictures. So you can get your message across loud and clear, wherever it needs to be seen.

Benefits

Simply more life-like - the displays come with a wide colour gamut showing every colour with much greater accuracy.

Business hours operation time - 16/7 with 350 to 400 cd/m² brightness.

Instant plug & go – with the built-in USB MediaPlayer slideshows of 4K Ultra HD photos and videos as well as music can be played, no need to connect a separate PC or other hardware.

Control made simple – using an integrated LAN/RS-232C interface all your displays can easily be controlled and monitored from a single PC.

Real impact - with built-in speakers, support for USB playback and range of connectivity, it is easy to create digital signage.

Product Information

Product Name	Sharp PN-HW751
Product Group	LCD 75" Essential Large Format Display
Order Code	60005532

Display

Panel Technology	TFT with Edge LED backlights
Active Screen Area (W x H) [mm]	1,781.8 × 1,002.2
Screen Size [inch/cm]	75 / 189
Aspect Ratio	16:9
Pixel Pitch [mm]	0.429 x 0.429
Brightness [cd/m²]	400
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	Standard (3)
Supported Orientation	Landscape; Portrait

Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768;	1280 x 960;	1680 x 1050;	640 x 480;
	1280 x 1024;	1360 x 768;	1920 x 1080;	800 x 600;
	1280 x 720;	1400 x 1050;	3840 x 2160;	848 x 480
	1280 x 800;	1440 x 900;	4096 x 2160;	

Connectivity

	1
Input Video Analogue	1 x VGA
Input Video Digital	3 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	3 x HDMI
Input Control	LAN 100Mbit; RS232
Input Data	1 x USB Medaplayer
Output Audio Analogue	1x Cinch (L/R)

Electrical

Power Consumption [W]	255 (max.)
Power Savings Mode [W]	< 0.5; < 1 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

Mechanical

Dimensions (W x H x D) [mm]	1,680 x 959 x 65.5
Weight [kg]	55
Bezel Width [mm]	15 (bottom); 15 (left and right); 15 (top)
VESA Mounting [mm]	4 holes; 600 x 400 (FDMI); M6
Packaging Dimensions (W x H x D) [mm]	1,832 x 1,283 x 280
Packaging Weight [kg]	69

Green Features

|--|

Additional Features

ASCII Control Commands; CEC Support; Removable Logo; Scheduler; USB Media Player
Black Front Bezel, Black Back Cabinet
CE; EAC; RoHS
Integrated Speakers (2 x 10 W)
2x AAA batteries; CD-ROM (User Guides/Manuals); Display; Logo Sticker; Power Cable; Remote Control; Setup Manual
3 years warranty incl. backlight; on-site service; optional 4. + 5. year warranty extension 1
16/7
ASCII Control Commands; HDMI CEC; Scheduled Timer

¹ please refer to terms and conditions of warranty extensions



This document is $\ensuremath{\mathbb C}$ 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023