

Sharp PN-HY431  
LCD 43" Midrange Large Format Display

## Datasheet

SUN	MON	TUE	WED	THU	FRI	SAT
	MEETING		KICK OFF		KICK OFF	
	PLAN REVIEW	MEETING	TEAM	DEMO	TEAM SYNC	SESSION 2
	PLANNING SESSION	SESSION 1	WORKSHOP		REVIEW	
	DESIGN	DEMO Q&A	REVIEW	PARTY	PLANNING SESSION	
	WORKSHOP	PLANNING SESSION	PLAN REVIEW	WORKSHOP		
	REVIEW	DRINKS	MEETING	MEETING	PLAN REVIEW	
			Q&A	DEMO	PARTY	



### Clearly stand-out - where it matters most.

Enjoy the perfect combination of an exceptionally slim and stylish design, vividly clear 4K pictures and powerful standalone operation with Sharp's PN-HY digital signage displays.

It makes them the ideal choice for signage and information sharing in a wide range of retail and corporate environments, including meeting rooms and reception areas, as well as food & beverage outlets and leisure establishments.

## Benefits

**Simply more life-like** - the displays come with a wide colour gamut showing every colour with much greater accuracy.

**Operation around the clock** - 24/7 with 500 cd/m<sup>2</sup> brightness.

**Instant plug & go** - with the built-in USB MediaPlayer slideshows of 4K Ultra HD photos and videos as well as music can be played, no need to connect a separate PC or other hardware.

**Control made simple** - using an integrated LAN/RS-232C interface all your displays can easily be controlled and monitored from a single PC.

**All the flexibility you need** - the display can be wall mounted in either landscape or portrait mode as well as face-down on a ceiling or face-up on a table or floor.

## Product Information

Product Name	Sharp PN-HY431
Product Group	LCD 43" Midrange Large Format Display
Order Code	60005554

## Display

Panel Technology	TFT with Direct LED backlights
Active Screen Area (W x H) [mm]	941 x 529
Screen Size [inch/cm]	43 / 107
Aspect Ratio	16:9
Pixel Pitch [mm]	0.245 x 0.245
Brightness [cd/m <sup>2</sup> ]	500
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	Pro (25)
Supported Orientation	Face Down; Face Up <sup>1</sup> ; Landscape; Portrait

## Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 800;	1280 x 960; 1360 x 768; 1400 x 1050; 1440 x 900;	1680 x 1050; 1920 x 1080; 3840 x 2160; 4096 x 2160;	640 x 480; 800 x 600; 848 x 480

## Connectivity

Input Video Analogue	1 x VGA
Input Video Digital	3 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	3 x HDMI
Input Control	LAN 100Mbit; RS232
Input Data	1 x USB Medaplayer

## Electrical

Power Consumption [W]	100 (max.)
Power Savings Mode [W]	< 0.5; < 1 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz; internal

## Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

## Mechanical

Dimensions (W x H x D) [mm]	973 x 561.2 x 63.5
Weight [kg]	11.5
Bezel Width [mm]	13.9 (bottom); 13.9 (left and right); 13.9 (top)
VESA Mounting [mm]	200 x 200 (FDMI); 4 holes; M6
Packaging Dimensions (W x H x D) [mm]	1,070 x 680 x 141
Packaging Weight [kg]	14

### Green Features

Energy Efficiency	Energy consumption: 90 kWh/1000 h; Energy efficiency class: G; LED backlight
-------------------	--

### Additional Features

Special Characteristics	ASCII Control Commands; CEC Support; Removable Logo; Scheduler; USB Media Player
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	CE; EAC; RoHS
Audio	Integrated Speakers (2 x 10 W)
Shipping Content	2x AAA batteries; CD-ROM (User Guides/Manuals); Display; Logo Sticker; Power Cable; Remote Control; Setup Manual
Warranty	3 years warranty incl. backlight; on-site service; optional 4. + 5. year warranty extension <sup>2</sup>
Operating Hours	24/7
External Control	ASCII Control Commands; HDMI CEC; Scheduled Timer

<sup>1</sup> adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

<sup>2</sup> please refer to terms and conditions of warranty extensions



CE



RoHS

This document is © 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023