

Sharp PN-HY501 LCD 50" Midrange Large Format Display

Datasheet





Clearly stand-out - where it matters most.

Enjoy the perfect combination of an exceptionally slim and stylish design, vividly clear 4K pictures and powerful standalone operation with Sharp's PN-HY digital signage displays.

It makes them the ideal choice for signage and information sharing in a wide range of retail and corporate environments, including meeting rooms and reception areas, as well as food & beverage outlets and leisure establishments.

Benefits

Simply more life-like - the displays come with a wide colour gamut showing every colour with much greater accuracy.

Operation around the clock - 24/7 with 500 cd/m² brightness.

Instant plug & go – with the built-in USB MediaPlayer slideshows of 4K Ultra HD photos and videos as well as music can be played, no need to connect a separate PC or other hardware.

Control made simple – using an integrated LAN/RS-232C interface all your displays can easily be controlled and monitored from a single PC.

All the flexibility you need - the display can be wall mounted in either landscape or portrait mode as well as face-down on a ceiling or face-up on a table or floor.

Product Information

Product Name	Sharp PN-HY501
Product Group	LCD 50" Midrange Large Format Display
Components	60005555
Order Code	60005555

Display

Panel Technology	TFT with Direct LED backlights
Active Screen Area (W x H) [mm]	1,095 x 616
Screen Size [inch/cm]	50 / 125
Aspect Ratio	16:9
Pixel Pitch [mm]	0.285 x 0.285
Brightness [cd/m²]	500
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	Pro (25)
Supported Orientation	Face Down; Face Up ¹ ; Landscape; Portrait

Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768;	1280 x 960;	1680 x 1050;	640 x 480;
	1280 x 1024;	1360 x 768;	1920 x 1080;	800 x 600;
	1280 x 720;	1400 x 1050;	3840 x 2160;	848 x 480
	1280 x 800;	1440 x 900;	4096 x 2160;	

Connectivity

Input Video Analogue	1 x VGA
Input Video Digital	3 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	3 x HDMI
Input Control	LAN 100Mbit; RS232
Input Data	1 x USB Medaplayer

Electrical

Power Consumption [W]	110 (max.)
Power Savings Mode [W]	< 0.5; < 1 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

Mechanical

1,128 x 649 x 63.5
15
14.9 (bottom); 14.9 (left and right); 14.9 (top)
4 holes; 400 x 400 (FDMI); M6
1,230 x 800 x 142
18.5

Green Features

Energy Efficiency	Energy consumption: 100 kWh/1000 h; Energy efficiency class: G; LED backlight

Additional Features

Special Characteristics	ASCII Control Commands; CEC Support; Removable Logo; Scheduler; USB Media Player	
Colour Versions	Black Front Bezel, Black Back Cabinet	
Safety and Ergonomics	CE; EAC; RoHS	
Audio	Integrated Speakers (2 x 10 W)	
Shipping Content	2x AAA batteries; CD-ROM (User Guides/Manuals); Display; Logo Sticker; Power Cable; Remote Control; Setup Manual	
Warranty	3 years warranty incl. backlight; on-site service; optional 4. \pm 5. year warranty extension 2	
Operating Hours	24/7	
External Control	ASCII Control Commands; HDMI CEC; Scheduled Timer	

¹ adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

² please refer to terms and conditions of warranty extensions





CE

RoHS

This document is $\ @$ 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.11.2023